ككر

NASA TECHNICAL MEMORANDUM

NASA TM 82432

ATMOSPHERIC OBSERVATIONS FOR STS-1 LANDING

(NASA-IM-82432) ATMCSPHERIC OBSERVATIONS FOR STS-1 LANDING (NASA) 62 p HC A04/MF A01 CSCL 04B

No 1-30740

Unclas G3/47 27184

By Robert E. Turner, James E. Arnold, and Gregory S. Wilson Space Sciences Laobratory

May 1981

NASA



George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama

_			TECHNICAL	L REPORT STANC	ARD TITLE PAGE
1.	REPORT NO.	2. GOVERNMENT AC		3. RECIPIENT'S C	
<u> </u>	NASA TM-82432				
4.	TITLE AND SUBTITLE			5. REPORT DATE	
1	Atmospheric Observations for	STS-1 Landing		May 1981	CANITATION COOF
				9, PERFORMING ON	GARIZATION CLOE
7.	AUTHOR(S)			A PERFORMING ORG	ANIZATION REPORT
	Robert E. Turner, James E. A	rnold, and Gr	egory S. Wilson	0.	
9.	PERFORMING ORGANIZATION NAME AND A			10. WORK UNIT NO.	
	George C. Marshall Space Fli	aht Center			
	Marshall Space Flight Center		2	11. CONTRACT OR G	RANT NO.
•	at shall opace illight center	, Alabama 5501	-		
				13. TYPE OF REPOR	& PERIOD COVERED
12.	SPONSORING AGENCY NAME AND ADDRESS	3		Tachmical	Memorandum
•	Alakiana 1 Assessable 1 and Co.			Technical	Memorandum
	National Aeronautics and Spa	ice administrat	ion		
	Washington, D. C. 20546			14. SPONSORING AC	ENCY CODE
	CHOOL PLANTAGY				
15.	SUPPLEMENTARY NOTES				
	Universities Space Research	Association			
	Prepared by Space Sciences I	aboratory, Sci	ence and Engineer	ing Directora	te
16.	ABSTRACT				
	The techniques and methods and aloft for flight verific Ldwards Air Force Base are s	cation of the S	TS-1 Orbiter duri	ing its descen	t into
<u>.</u>	MEL WORDS				
17.	KEY WORDS	į	18. DISTRIBUTION STAT	EMENI	
		İ			
1			Unclass	sified — Unli	mited
		İ		0 1	
			Robert (7 June	✓
		i	1 cover	_,	=
		ļ			
19.	SECURITY CLASSIF, (of this report)	20. SECURITY CLAS	SIF, (of this page)	21. NO. OF PAGES	22. PRICE
	Unclassified	Unclass	ified	61	NTIS

1.2. 1. 1.

4 1.5

ACKNOWLEDGMENTS

The authors thank Messrs. Wade Batts, Computer Sciences Corporation, and John Hickey, Atsuko Computing International, for their assistance in processing the upper air data used in producing the Meteorological Data Tape.

The authors also thank Mr. Luke Gilchrist, University of Tennessee Space Institute, for supervising the taking of the observations by FWG Associates personnel and other members of the Atmospheric Sciences Division.

TABLE OF CONTENTS

		Page
Ι.	INTRODUCTION	1
11.	GENERAL SYNOPTIC CONDITIONS AT LANDING TIME	1
111.	DISCUSSION OF BASIC DATA	3
	A. Collection of the Data and the Data Acquisition System	3
	B. Methods of Processing	3
IV.	DISCUSSION OF UPPER AIR DATA	4
	A. Accuracy Estimates	4
	B. Tabulated Data	5
REFE	RENCES	19
APPE	ENDIX A. CONTACT DATA	21
APPE	ENDLY B. 30 SECOND DATA	39

LIST OF ILLUSTRATIONS

Figure	Title	Page
1.	Large-scale analysis of weather conditions over North America and the U.S., including surface map, 500 mb (>18,000 ft) height contours, high and low surface temperatures, and 24-h precipi- tation map for 1200 GMT 14 April 1981	8
2.	GOES-W infrared satellite image at 1815 GMT 14 April 1981. Clouds are shown in white	9
3.	GOES-Wimage-enhanced infrared satellite image at 1815 GMT 14 April 1981	10
4.	GOPS-W infrared satellite image at 1815 GMT 14 Apr. 1981. Superimposed are wind barbs (m/s) and a geopotential height analysis (m) for 500 mb (~18,000 ft) from data at 1200 GMT 14 April 1981.	11
5.	700 mb (≤ 10.000 ft) winds (m/s) and geopotential height analysis (m) from data at 1200 GMT 14 April 1981.	12
6.	500 mb (*18,000 ft) winds (m/s) and geopotential height analysis (m) from data at 1200 GMT 14 April 1981	13
7.	300 mb (>30,000 ft) winds (m/s) and geopotential height analysis (m) from data at 1200 GMT 14 April 1981	14
8.	200 mb (55,000 ft) winds (m/s) and geopotential height analysis (m) from data at 1200 GMT 14 April 1981	15
9.	Visible GOES W satellite image at 1815 GMT 14 April 1981 over southern California	16
10.	Vertical profiles of wind barbs (m/s), temperature (solid line in °C), and dew point temperature (dashed line in °C) from the surface to 100 mb (~55,000 ft) at 1200 GMT 14 April 1981 for Edwards Air Force Base	17
11.	Ground track of STS 1 landing trajectory over northern California. Rawinsonde sites are located at large black circles. Wheeler Ridge is on the left side of the track, while Tehachapi is on the	••

LIST OF TABLES

Table	Title	Page
1.	Estimates of the RMS Errors in Thermodynamic Quantities	5
2.	Estimates of RMS Errors in Wind Data	5
3.	Example of Contact Data	6
4.	Explanation of Column Headings of Tabulated Sounding Data for the STS 1 Orbiter During Its Descent and Landing	7

TECHNICAL MEMORANDUM

ATMOSPHERIC OBSERVATIONS FOR STS-1 LANDING

I. INTRODUCTION

The successful launch and landing of the Space Shuttle concluded the first phase of NASA's space vehicle/flight program. This report presents a summary of synoptic conditions and the atmospheric observations taken in support of the Sonic Boom Measurement Program and flight verification of the STS-1 Orbiter.

The Space Shuttle STS-1 was launched from Complex 39A at the Kennedy Space Center, Florida, into a nominal 150/150 nautical mile altitude circular orbit on April 12, 1981.

The deorbit maneuver was initiated at approximately 53 hours, 31 minutes, ground elapsed time during the 36th orbit, with subsequent landing on Rogers Lake bed at Edwards Air Force Base, California, on April 14, 1981. Runway 23 was the primary runway, 17 was the backup, and 04, the alternate.

This document is written under the requirement Level II PRCB, dated May 5, 1980, Request S-13705A, to furnish atmospheric data at the surface and aloft for flight verification of STS-1 Orbiter during its descent into Edwards Air Force Base, California.

II. GENERAL SYNOPTIC CONDITIONS AT LANDING TIME

Deorbit maneuvers for STS-1 were initiated at 1731 GMT April 14, 1981, while passing over the western portion of the North Pacific Ocean. The Shuttle Orbiter then descended into the atmosphere, passing rapidly through the stratosphere and then the troposphere over Southern California. It landed at 1818 GMT at Edwards Air Force Base. This section describes the general synoptic conditions during this period. These conditions were derived using both satellite imagery (visible and infrared data from the GOES-W satellite) and conventional surface and upper-level rawinsonde measurements of temperature, winds, moisture, and pressure. Analysis of these data was performed by the Man Computer Interactive Data Access System (McIDAS) in the Space Sciences Laboratory of the Marshall Space Flight Center.

Overall synoptic conditions for the STS-1 landing were optimal considering winds aloft and at the surface as well as visibility along the glide slope. The central and western United States was dominated by a large

high pressure cell, as shown in Figure 1. A major cyclone had moved through the central U.S. and was located over the Great Lakes. Aviation weather in that region was poor, with low ceilings, poor visibility, and moderate precipitation developing along the frontal zone and around the low pressure area. Fortunately, this system had developed and moved east of the landing site 24 to 36 hr prior to landing.

Figures 2 through 4 show infrared satellite images over the western United States at 1815 GMT. State and geographical boundaries are superimposed. These figures show that skies were completely cloudless both over and west of Edwards Air Force Base. This can be supported by image enhancement of the black and white image in Figure 3 where clouds would be represented by dark green, reds, and white. The 500 mb (5000 m/18,000 ft) wind barbs (m/s) and a geopotential height analysis (decameters) superimposed in Figure 4 show very light wind conditions (10 m/s) in the middle troposphere from the southwest, which is supported by the weak gradient of geopotential height over the landing area.

This pattern of weak winds and gradients in the height field extended throughout the troposphere. This is shown in Figures 5 through 8, which display wind barbs and geopotential height analyses for 700 mb (~ 3000 m/ 10,000 ft), 500 mb (~ 5000 m/18,000 ft), 300 mb (~ 9000 m/30,000 ft), and 200 mb ($\sim 12,000$ m/40,000 ft), respectively, over the western United States. No frontal zones were present along the glide slopes, but a weak upper-level disturbance with high cloudiness was moving northeast through Arizona and New Mexico. This system had passed over the landing site during the previous 24 hr period.

Figure 9 shows a full-resolution (1 km) visible picture of the Edwards area (small cross) also at 1815 GMT on April 14. Snow over the southern Sierra Mountains is seen toward the upper left, and low cloudiness (< 2000 ft AGL) is evident over the cold ocean water off the southern California coast. Skies were clear over and surrounding the landing site. Light surface winds and excellent visibility prevailed along the California portion of the final ground track.

Figure 10 is a plot of the vertical distribution of winds (m/s), temperature (solid line in °C), and dew-point temperature (dashed line in °C) at 1200 GMT April 14 taken at Edwards Air Force Base. The profiles extend from the surface to 100 mb (~ 17,000 m/55,000 ft). Winds speeds are light (-15 m/s) at all levels associated with weak vertical wind shears aloft. The temperature structure is statically stable or near neutral at all levels. Turbulence in clear air was, therefore, unlikely. The temperature/dew-point temperature spread is such that relative humidities were less than 50 percent at all levels.

In summary, landing weather for STS 1 was unusually optimal considering the active nature of weather disturbances that traverse that area during the spring season.

III. DISCUSSION OF BASIC DATA

A. Collection of the Data and the Data Acquisition System

Past experience gained on Apollo and Skylab programs has shown that it is necessary to have atmospheric data to verify the analytical techniques used for engineering analysis. For this reason, atmospheric data at the surface and aloft were obtained by using the Rawinsonde System. One Rawinsonde System was placed at Wheeler Ridge and a second one at Tehachapi, California. These sets were positioned along the STS-1 reentry track shown in Figure 11. The requirements to collect atmospheric data approximately 2 hr before landing and at the time of landing from these two locations have been met.

The Rawinsonde System is a transportable radio direction finder designed to track a balloon-borne radiosonde automatically. A radiosonde signal containing information about the atmosphere in the form of an amplitude or frequency modulation data signal is received, amplified, and detected by this system. The detected signal is passed to separate equipment in the system where it is recorded. By reference to calibration data for the radiosonde, this recorded information is converted to values of temperature, humidity, and pressure. Recordings of time versus progressive changes of the elevation and azimuth positions of the ascending balloon package, as determined by tracking of the signal from the radiosonde, are made so that they can later be converted to wind speed and direction.

The radiosonde consists of a transmitter, modulator, antenna, battery, and pressure, temperature, and humidity sensing elements. The radiosonde, parachute, and train weigh approximately 2 kg (4 lb) and can be carried to an altitude of approximately 30 km by a helium-filled balloon. The battery furnishes power to the modulator and transmitter. The transmitter operates in the 1660 to 1700 MHz band; and its carrier is amplitude modulated by an audio-frequency pulse, the rate of which is determined by the pressure, temperature, and humidity sensing elements.

The Rawinsonde antenni automatically tracks the balloon-borne radiosonde by continuous homing on the radiosonde signal to horizontal distances of approximately 200 km and altitudes of up to 30 km. The equipment recorder records the elevation and azimuth angles of the position of the radiosonde versus time.

B. Methods of Processing

The procedure used to compute the soundings is described by Fuelberg [1] and Turner [2]. All raw data keypunched were checked for errors by calculating centered differences on the input data. Additional checks include centered differences on computed winds and checks on lapse rates of computed temperatures and dew points. Suspected errors were checked with the original recorder chart information and the appropriate corrections made.

The final data set consists of data computed at each pressure contact as well as data at 30-sec intervals. Thermodynamic quantities were computed at each pressure contact, while winds were computed from the available 30-sec interval angle data by means of centered finite differences. Winds were subsequently interpolated to each contact.

The following procedures were employed in the processing of these data which differ from those described by Fuelberg [1]:

- 1) Humidity values, including dew-point temperature, were computed only at temperatures above -40°C; at temperatures below -40°C, humidity values are missing and are indicated by a field of nines. Moisture values were computed if the relative humidity exceeded 1 percent. If the value was below 1 percent, it was set equal to 1 percent and used in the computation of other moisture variables.
- 2) Winds based on low elevation angles are denoted by asterisks. One asterisk denotes angles less than 10° but greater than 6° , while two asterisks denote angles less than 6° . Caution must be exercised in the use of data at low elevation angles, since it is subject to rather large RMS errors.
- 3) Wind direction and speed were determined for contact levels by interpolating time values.

In precessing the data, corrections were made for any errors made in recording the observational data.

IV. DISCUSSION OF UPPER AIR DATA

A. Accuracy Estimates

Estimates of the RMS errors in the wind and thermodynamic quantities of the STS-1 descent rawinsonde soundings are the same as those given by Fuelberg [1]. The error estimates for thermodynamic variables are presented in Table 1.

The RMS errors for wind speed and direction are difficult to describe since they are a function of tracking geometry and other factors. Maximum RMS errors for winds (speed and direction) computed at 30 sec intervals (based on the worst geometric tracking configuration) for 10 and 40 degree elevation angles are presented in Table 2. The accuracy of the wind data at pressure contacts is greater than that stated for the 30-sec winds because of the added smoothing and interpolation performed. In addition, the errors stated for the 30-sec winds were maxima for the stated conditions.

TABLE 1. ESTIMATES OF THE RMS ERRORS IN THERMODYNAMIC QUANTITIES

Parameter	Approximate RMS Error
Temperature	0.5°C
Pressure	1.3 mb from surface to 400 mb 1.1 mb between 400 and 100 mb 0.7 mb between 100 and 10 mb
Humidity	10 percent
Pressure Altitude	10 gpm at 500 mb 20 gpm at 300 mb 50 gpm at 50 mb

TABLE 2. ESTIMATES OF RMS ERRORS IN WIND DATA

	RMS Erro		RMS Errors in Dire	
Pressure mb	10-degree elevation	40-degree elevation	10-degree elevation	40-degree elevation
700	2.5	0.5	9.5	1.3
500	4.5	0.8	13.4	1.8
300	7.8	1.0	18.0	2.5

B. Tabulated Data

An example of the contact data is given in Table 3, with the explanation of column headings in Table 4. The first line of data for the time 0.0 min is surface data. The three numbers in the upper right-hand corner are the number of pressure levels computed, the minimum pressure obtained (mb) and an identifier with the value 0 for 30-sec angle input and 1 for 1-min angle input.

The contact data and the 30-sec data are presented in Appendices A and B.

TABLE 3. EXAMPLE OF CONTACT DATA

The second second of

いち かっ 無人のないないというとうかい

STATION NO. 2 UNEELER RIDGE, CALIF

						:	APPIL 1815 GRT	1961					•	5	•
A 22	CMTCT	ME LOWT	2 E	TENP SC C	06 e e 1	* 50	SPEED M/SEC	U COMP	A COMP	707 7 7	E POT 4	MX MTO	ΞĮ	PANCE	28
•	•	1,63	1002.0	28.6	9	330.0	en.	M	•	295 6	313.7				•
Ŋ	•		999.0	21.4	8	296.7	'n	*	;	294.6	312.8		42.1	•	2
٠.	•	201.0	969.	20.3	4.4	283.3	۲.	•		294.4	312.0	9.9	43.8	•	ż
•	•	3.60.5	479.	9.5	9.9	1000	Φ.	ć.	7.5	.	311.	m;		•	ř
m.	•	463.4	969.	6.7	r.	237.5	• -	٠.	r.	293.8	309.9		₩. ₩.	-	<u>*</u>
<u>.</u>	•		127.	-2.	l-,	291.7	ħ.	•	ų.	293.9	314.2	•.	47.2	-	÷
~	2.	652.6	947.0	. . .	9 .	257.8	ķ	ņ	•	294.0	309.2		46.0	-	=
٠, د.	. A.		936.0	4.0	(·•	198.2	Ģ	'n.	ė	294.1	309.1	ب ن	47.4	•	ż
٠, د.	.4.	645.9	926.	5.0	Ø .	169.6	m.	-	ų	294.6	316.5	ø.	20.4	-	ž
3.5	. e	934.8	916.±	4.6	n.	92.7	Ģ	٠.	•	295.1	310.0	.	9. 9.	-	ä
~	•	1627.6		m.+	7	122.1	~	Ņ	Ξ,	295.6	311.2	1 0	30.7	•	2
•		121.3	•	. m	e.	194.9	'n	•		× ×	. I	5.7	5. S	-	ŗ
		1215.9		n, n	e.	167.4	T.		m m	200	35.1	9.	51.2	-	ä
•		1321.2	875.0	6.9	œ.	151.3	•	4	M.	236.2	314.0		30.5	ú	£
.	20.0	1418.8		e. 6	in i	132.8	(N)		Ç	7	316.2	m.	40.7	ú.	Ž
PO 1	21.0	1517.1	938.	9.0	•	57.0	o		9 1	302.0	. O. E.	2.4	20.0	•	3
, .	22.	A. 9491	946.	•	-7.3	134.9	m.	6. P	6	302.1	369.	%	20.0	•	Ē,
-	23.0	1707.		P. 19	n ·	4. BB.		٠, U	*	302.1	7		21.9	•	ž
	24.0	7.00	#26. E	- M	9	121.3	۸۰۶	0.P	.	362.3	M	*	22.4		ň
•	C :	P.0161	9.5	M .	2.7	129.0	9 . 6	9	* 1	302.0	330.0	91	23.9	= :	322
» i	. 92	2013.5	•	6.	9.7.	28.0		•	- 0	363.2	211.1	,	24.0		2
	27.	2117.7		* .	•	127.7	•		2.0	362.7	310.2	9.0	25.7		
N .	- 42	2722.7		n	•	125.9	n :	•		302.8	336.4	·	27.4	•	212
•	27.0	2328.7	700.0		M (125.4	۰. ۱ م		e c	1000	0.01P	• I	28.9	- (
· •		2647								7,7	7.	n 1			
		6333.	247		? •	27.7				7 247					
	11	2741.2	7.10			20.00		-2-	4	707	700	~	¥.		
-	34.0	2052.2	726.0		8.11-	132.4	*	-6.2	2.3	363.4	400.0		31.5	-	
E. E	2	2953.1	719.0	H. W	-12.9	140.6	6.7	-5.6	6.7	363.5	369.4	9 .0	23.7	Ä	
Z: _	36.0	3055.1	710.0	. w	-14.4	146.9	9 .6	-6.2	•	304.6	309.9	•	26.3	,	
- 2	37.	3169.0	7.	2.5	¥.	153.3	10.3	*	×.	4. T	316.3	-	27.5		
		3274.1	691.	<u>*</u> :	• •	9.09.	•	m.	6	702	M10.0	• !	23.9	- '	
•		12/3.0		•		7.44	•					?•			
		*	7	-	-22	145		•		307	316.1				
	6.04	170.	***		-23	. 631			4	*	7	•			9
		No. of the last	***		-24.6	30.0	4.4	9	M	367.1	7.00	•		•	2
		3424.3	417	M	-25.3	,		7	M	107.3	300.7	•			325
18.4	45.	4026.0	628.		-26.2	149.3	7	-2.2	7.7	307.5	309.0	^	15.6	•	322
-	*	4150.5	619.0		-26.8	147.4	4.7	-2.5	•	397.8	316.1	٠.	5.0	8	2
16.6	47.0	4265.6	616.0	-5.1	-27.1	133.1	9 .9	-2.4	•	308.8	111.4	٠.	13.8	,	4
12.1	•	4302.2	9 . 1. 9	10. U	-27.4	161.5	•.•	4.1	5.7	369.6	311.0	۲.	13.0	5	355
17.5	+	4388.4	592.0		-27.5	169.6	•	7.	*· ·	310.2	312.4	۲.	1.4	•	2
17.9		**	. 1	* ·•	-27.7	176.9	9 .	ŗ.	8.5	310.7	3:2.9	٠.		'n	7

* BY TEMP MEANS TEMPERATURE OF TIME MANE BEEN INTERPOLATED ** BY TEMP MEANS TEMPERATURE OF TIME MANE BEEN INTERPOLATED ** BY SPEED MEANS ELEVATION AMOLE LESS THAN 4 DEC

TABLE 4. EXPLANATION OF COLUMN HEADINGS OF TABULATED SOUNDING DATA FOR THE STS-1 ORBITER DURING ITS DESCENT AND LANDING

1		
	TIME (MIN)	Time after balloon release.
	CNTCT	Contact number.
	HEIGHT (GPM)	Height of corresponding pressure surface in geopotential meters.
	PRES (MB)	Pressure in millibars.
	TEMP (DG C)	Ambient temperature in degrees Celsius. NOTE: An asterisk indicates that time from release and/or temperature were linearly interpolated.
	DEW PT (DG C)	Dew-point temperature in degrees Celsius.
	DIR (DG)	Wind direction measured clockwise from true north and is the direction from which the wind is blowing.
	SPEED (M/SEC)	Scalar wind speed in meters per second. NOTE: An asterisk indicates that wind quantities are based on an elevation angle that is between 10° and 6°. A double asterisk indicates that the elevation angle is less than 6°.
	U COMP (M/SEC)	The E-W wind component, positive toward the east and negative toward the west.
	V COMP (M/SEC)	The N-S wind component, positive toward the north and negative toward the south.
	POT T (DG K)	Potential temperature in degrees Kelvin.
	E POT T (DG K)	Equivalent potential temperature in degrees Kelvin.
	MX RTO (GM/KG)	Mixing ratio in grams per kilogram.
	RH (PCT)	Relative humidity in percent.
!	RANGE (KM)	Distance balloon is from release point along a radius vector.
	AZ (DG)	Direction toward balloon measured clockwise from true north.

The state of the s




Figure 1. Large-scale analysis of weather conditions over North America and the U.S., including surface map, 500 mb (approximately 18,000 ft) height contours high and low surface temperatures, and 24-hr precipitation map for 1200 GMT 14 April 1981.



OBJETNAL PAGE IS OF POOR QUALITY

Figure 2. GOES Winfrared satellite image at 1815 GMT 14 April 1981. Clouds are shown in white.



Figure 3. GOES-W image-enhanced infrared satellite image at 1815 GMT 14 April 1981.



08/07/41 P198/18

Figure 4. GOES-W infrared satellite image at 1815 GMT 14 April 1981. Superimposed are wind barbs (m/s) and a geopotential height analysis (m) for 500 mb (~18,000 ft) from data at 1200 GMT 14 April 1981.





Figure 5. 700 mb (~10,000 ft) winds (m/s) and geopotential height analysis (m) from data at 1200 GMT 14 April 1981.



· Water and the same

500 mb (~18,000 ft) winds (m/s) and geopotential height analysis (m) from data at 1200 GMT 14 April 1981. Figure 6.




Figure 7. 300 mb (~30,000 ft) winds (m/s) and geopotential height analysis (m) from data at 1200 GMT 14 April 1981.





Figure 8. 200 mb ($\sim 55,000$ ft) winds (m/s) and geopotential height analysis (m) from data at 1200 GMT 14 April 1981.



Figure 9. Visible GOES-W satellite image at 1815 GMT 14 April 1981 over southern California.



· •

Figure 10. Vertical profiles of wind barbs (m/s), temperature (solid line in °C), and dew-point temperature (dashed line in °C) from the surface to 100 mb (∿55,000 ft) at 1200 GMT 14 April 1981 for Edwards Air Force Base.




Figure 11. Ground track of STS-1 landing trajectory over northern California. Rawinsonde sites are located at large black circles. Wheeler Ridge is on the left side of the track, while Tehachapi is on the right.

REFERENCES

- Fuelberg, H.E.: Reduction and Error Analysis of the AVE II Pilot Experiment Data. NASA Contractor Report CR-120496. Marshall Space Flight Center, Alabama, 1974.
- 2. Turner, R.E.: The Mechanics of Atmospheric Systems Derived Through Vertical and Horizontal Analysis of Parametric Data, NASA Technical Paper 1072. Marshall Space Flight Center, Alabama, 1977.

APPENDIX A

Contact Data

PRECEDING PAGE BLANK NOT FILMED

CAL IF	Ĕ
STATION NO.	14 MPRJL 1535 GMT

						±	1535 CAT	<u>.</u>							•
													•	:	•
# H	CMTCT	MEICHT		10.0	DEE PT	# 10	35660	- COMP	× 00H	1 10	E P01 T	AX ATO	Ī	RAMGE	74
I E		5	£	ں لا	ပ 9	ဗ္ဓ	M/SEC	1.9EC	M/8EC	¥	×	3×5	L 04	¥	2
•	6.7	160.0	1.001.4	17.0	•	350.0	•	-:	s.	290.0	308.6	7.1	98	9	•
**	۸.	265.5	33 7.		•	300.3	₹.	P.	?!	289 7	304.1	*	***	•	132
•	•	239.7	• •	13.4	*	206.3	M.	m	-	209.0	303.0		47.1		52
•	•	7.96	976.	4.6	N P	238.5	'n	M	٠.	209.0	5.50	, m	47.7	•	122
1.2	• .	• •	965.	•	r: m	239 7	•	7.	₽?	291.2	NOW. 7	•	P . 07	•	
 5	• :	576.6	954 . 6	<u>-</u>	¥.	243.3	8 .8	39	•.	291.1	W. 448	-	46.7	9	ŝ
•	12.	667.5		13.0	e. M	244.9	'n	0	•	291.8	700	en	10	-	99
8 .8	13.0	766.2	933.0	13.5	7.6	243.5	. c	F	۲.	292.4	106.7	m	51.2	-	9
7.8	14.0	6.36.9	923.0	13.1	7. M	233.7	٠	s.	ij	292.9	307.0	8	6.0	•	3
• · ·	13.0	427.7	912.0	12.5	2.7	. 9.	so.	♥ :	- .	293.5	307.4		8.0	-	,
4 .2	• .	1950.3	915.	12.3	¥.	14.5	۲.	•	7	294.0	306.7	4.0	4.4	-	;
9.0	- 1	1143.6	55 . •	1.2	9. •	135.3	•	₹. 1	₹.	293.8	307.9	6) (4)	33.6	-	ñ
e.	•	1247.1	- 2	• •	2	63.0	Ģ		-	27.2	7 P. 7	 m	56.2	₹.	•
T .	•	1342.3	•71.	•.	- m	49.7		•	۲.٦	295.2	310.2	87. 87.	59.7	•	
. .	5 0.	1424.5	• •	•	•	97.1	~	•. T-	ä	295.6	307.6	F. 7	- · •	-	
*	5 . 6	1346.	836.	12.9	-2.7	131.1	•	₩. ₩.	9. M	299.7	316.2	H. 7	33.7	- .	347.
9	83.0	1648.1	:	•	• •	135.7	- •	4.	FF ♥	499.7	306.9	7.7	22.4	Ņ	320
•	23.0	1735.		11.2	. 6 .	122.5	•	-5.8	۲. ۱	29%.8	306.4	~	22.5	e.	325
٠ •	24.0	1.926.1	621.	11.2	-9.2	14.7	٠,	17.4	4.6	300.8	307.7	m.	23.	'n	314.
•.4	.	1920.2	• :	•		115.9	F. 6	₹.	- .	301.5	309.0	9. 7	25.7	۲.	367
۲.	26.1	2041.5	• :	*·*	9	119.6	• •	- 8 .3	9.4	362.2	309.7	%	26.1	• -	305.
.	27.8	\$148.9	. <u>.</u>	٠.٧	7	122.9	n.	• · •	 0	302.5	310.1	3.6	27.4	1.2	Ĭ.
	20.0	2251 . 3	÷	•	r.	123.7	9.6	3 ·	T)	302.6	316.2	%	28 . 6	-	7
~ •	29.0	2357.7	771.	6 .7	9.	124.9	•	6.2-	5	302.7	310.4	9 .	99. 9	٦.6	304.
•	30.0	2465.1	761.	•	₩,₩	126.2	•	-7	u. v	362.7	310.5	2.7	32.7	* .	304.
•	• ·	2573.5	. E	†	M . 6-	127.5	•	• •	-	302.3	309.7	ei ei	33.6	•	305
•	22	2662.9	7 ·	+ .4	1.4.	126.9	• :	•	•	362.9	316.2	8.	33.2	2.3	303
•		2793.4	- T.	n	•	126.6	* .	- 5	•	305.6	316.0	2.3	37.0	%	700
N .	*	268	722.0	6 1	¥ .	126.9	- :	4	•	303.0	- O - M		37.	e i	
	2	27.27		- 1	6	128	m (6. i		3.7.6	3.69.5	N C	g:	- 1	
				P 4	7 1		P (m •		200	7.00		7	· ·	
												• •) a	
		77.75			-16.7	200		, ,		100	300		3	•	
12.6	•	1341.3		4.1-		137.0	•	7.5		365.5	309.5	m	24.7	*	309
12.9	•	3649.8	657.0	*, -	-22.8	E +91	7.7	-2.1	7.4	300	309.4	•	17.7	*	316.
7.7	42.0	3771	- 23	-2.2	23.6	177.9	7	4	٠ 9	306.9	309.8	•	17.4	n	3,1.
13.7	43.0	2878.5	639.4	-2.	-25	190.7	8	•	-	307.3	309.9	•	1.6.1	•.	313.
14.2	7	3962.7	636.	. H	-25 3	- 30.	9 .	6 0	9 .	317.7	310.2	•	16.3	9 . †	314.
•.•	+ ()	- 944	621.0	4.4	-26.4	170.4	+ . +		♥.	307.6	309.9	۲.	1.	4.7	316
• .	• .	4210.0	612.0	9	-27.0	166.2	4	• •	- •	3.99	31 6 .2	۲.	¥. 9 .	•	316.
÷.	• ^ •	4326.8	663 .	* . 9 -	-27.8	163.6	-	7.5	e. M	~ ~	310.W	•	¥. 9	•	317.
	•	M 7777	594.0	9.9	2	166.5	- •	•	♂	* *	31.3	•		9	317.
m .	•	4563.3	500	F. 2-	-28 9	177 2	•	N,	•	369.9	W. 1.	•	* · •	- -	8 6
·.	9.	7634	276 0	-7.8	-28.7	187.0	ъ	æ.	S	316.7	312.8	•	16.7	-	319.

• BY SPEEJ MEANS ELEVATION ANGLE BETWEEN 6 AND 10 DEC • BY TEWP WEANS TEMP"RATURE OF TIME MAVE BEEN INTERPOLATED •• BY SPEED MEANS ELEVATION ANGLE LESS THAN 6 DLG

œ	CALIF
94 KO	RIDGE,
STATE	HEELER RIDGE

· .

.

						<u>*</u>	APRIL 1535 GMT	1961					¥	E1 951	•
¥ E	CNTCT	HE I GHT GPH	e e	1636 00 C	DE P	919 90	SPEED	U COMP M/SEC	V COMP M/SEC	P01 + A	. POT 1 DC K	MX RTO GM/KG	¥ 5	RANCE	7 9 9 G
Ģ	91.	4792.7	360.0	1 .	-28.9	198.0	# M	-	m.	311.6	313.7	¥.	16.7	'n	320.
9.	52.0	4916.6	939.0	1-6-	-28.5	203.9	0 · M	- .	2.7	ø F	314.0	9.	10.0	'n	321.
•	53.0	5027.9	551.0	-10.0	-29.5	202.9	9.6	3 -	8,4	. ZIE	314.2	ě	6.0	'n	3 321.
•	34.0	5154.7	342.0	-10.7	-29.8	196.3	si Si	۲.	4	312.7	314.7	•	. e	en i	322
•	9.	5260.9	334.0	-11.7	₩.0E-	196.3	4	^	M.	912.9	4.4.0	٠	4.5		355
e i	98	90.00	32.0	4. i.	4. E	208.1	u u	-	٠. و. ا	113.0	314.8	nů (M ('n	323.
<u>.</u>	37.0	2010.7	9.7.0	6.51	52.3	4.6.5	N (•			314	ij.		ה	222
N.		2633.9	30.0	3.0	20.00	210.8	M (,	N (4.4.	ņ.			
•	9.0	4.553.4	9.70	7.01	7 7	9 (n v		, e	2.5.0	* * * *	į		. u	
•					9 1	9 0	9 10	Ì			4.0) H	106
• •		6121.2	427.0	-18	-36.3	200.1	9			314.4	315.6	•	. 6	w	326
, m	7	6262.8	469.0	-20.1	-36.9	213.6	-		7	314.5	318.6	M	20.6	'n	326.
9	4	6374.3	461.0	-21.2	-37.0	210.6	•	^	-	314.5	315.7	7	22.4	10	327.
2	15	6.583. A	453.0	-22.4	-36.9	205.4	9.	۲.	-	314.5	313.0	M	25.0	ın	327.
•	•	6617.4	446.0	-23.7	-37.2	206.8	•	•	-	314. H	315.5	m	27.3	'n	6 327
	67.0	6749.4	438.0	-24.9	-35.8	213.4	0.0	-	1.7	4.4.6	318.0	*	33.1	'n	
*		6883.1	430.0	-26.2	-37.1	227.3	-	m	÷.	314.4	315.6	₹.	34.7	'n	7 328.
•	69.0	7001.5	423.0	-27.7	-38 · 3	245.4	9	* :	•	J14.	315.1	7	35.3	'n	329.
5.3	70.0	7121.2	416.0	-29.0	-39.5	261.0	7.1	•	m.	41.0 0.0	314.9	ij	79.	'n	329.
5.7	2.0	7259.7	7 80 . 0	-30.3	-40.3	265.5	•	-	₹.	Ø .	11.	ņ	, 18 10 10	'n	330
	72.	7382.7	401.0	-30.6	. • • •	260.5	2. W		-	7. TH	418.7	ij.	7.96	vi (330
۲.	73.0	7525.5	394. O	-31.9	-	265.7	() ()	en e	ú.	9.00	919	i.	7.9	י מ	
œ.	74.0	7634	307.0	-32.7	-45.4	250.6	N (, i	SO !	212.5	316.3	ú.	7.9 1.9 1.0	'n	. 231
•	75.	7762.4	9	-33.7	+77	234.9	M ·		-	213.6	316.3	i,		n	
- !	2:	9.1.66	372.0	-74.0	P 44	228.4	w (- ·	• •	317.3	- 6	ú.	, i	'n	333.
ים ים		7	9	20.5	N	8.722	9 ·	- (? .	9 (,	:	, ,	
		4.00			7	4.752	N M	, o		7.9.5	317.5	ų -		n ir	
•		717	248	7.62-	9	262	M	M		316.6	217.1	-	7	w.	136
M		8573.0	778	-40.7	6	269.2	M	9.70	•	317.0	93.9	2.0	9.666	'n	337.
	2	***	332.0	-41.8	30.0	271.9	ri M	W.	;	317.1	939.9	99.9	999.9	'n	339.
m.	3 .	8617.8	326.0	-43.5	43.9	277.4	2.7	2.7	* :	316.9	\$30.0	93.3	999.9		5 339.
•	•	1.7964	319.0	B. 19	\$.0	203.0	, ,	8. S.	•	318.5	23.0	43.4	23.0	'n	139
~	9 2.	9091 . I	314.0	• · D • ·	\$	205.0	2.3	44 44	•	210.0			626	'n	
•	:	9220.3	307.0	7.97	6.66	277.7	M :	M (m .	918	220.0		999.9	ומו	
1.	97.0	9273.3	300.0	-47.0	6.0	277.4	o i	e i	•	219.1	200			Ď	
•	:	9567.0	294.0	5,74-	•	201.6	•. M	M	•	750 · 3	22.0	2.0	6.00	in (
-	•	\$643.8	286.0	M . 94-	6.66	204.0	*	M .		321.	20.0	2	9.00	in (7
•	90 .	9781.1	282.0	P .00-	•	269.4	m		-	120.1	6.0	6.6	999.	n i	
	• -	9921.2	276.0	-31.0	•	295.0	~ •	- •	Ξ.	321.0	939.9			n	
9.6	92.	. 199	276.0	-52.1	9.0	294.5	.	- ·		321.5	25.0			•	
•	94.0	10101	265.0	53.5	£ .	208.7		# ·	· ·	327.0	23.9			•	
n.	Į.	10332.0	259.0	-53.0	6.6	200.1	0.0	, . ,	- 1	322.	6.66		939.4	•	335
•	93.	1 9482 . 0	251.0	-33.4	99.4	277.8	0	•	P	322.	939.9		7.4	•	326.

SPEED MEANS ELEVATION ANGLE BETWEEN 6 AND 10 DEG Them Peans Tenecrature of Time Nave Been interpolated Design and the English Angle 1658 Than A DEG

176	CALIF
STATICA NO	

•	82	3	, 6CE	, v	, =		3.	77	8	35.	Ľ	36	42	1	\$	9	\$	3	Š	23	21	ž	7	8	8	ž	X	*	3	37	57.	3	Ř	į	Ř	Ì	7	2	ž	ż	Ŗ	2	Ŕ	Ŕ	R	S
156 13	PANCE		•	•			W.	E.4	*	4.5	9 . e	•	'n	8.0	n n	ø.	•	9.9	7.6	4.	9 ~	8.2	9.4	- '-	4.7	F. 1	16.6	11.2	11.0	12.5	13.1	2,6	# · ·	•		e i	13.7	16.1	26.6	17.1	17.6	10.3		19.4	20.0	20,5
ï	Ē	104				6.66	11.0	939.9	***	9.666	9.466	444.0	9.00	\$ 555	44.0	\$.555	4.666	***	499.4	939.9	***	23.0	959.9	4.66	6.666	999.9	\$3.9	\$3.0	959.9	***	***	•						400.0	\$?	**	9.0	4.04	***	•	·
	MX PTO	5	r 1	3		*	\$5.9	*	\$	2 .0		\$	љ З	2.0	ф. Х	\$	* *	***	2	3	2	*	2	2.0	\$	2	*	3 :	1	*	.	?		r.		_			2	*	?	•	*	2:	2	
	E POT T			0.505	***	25.0	9.55.9	***	466.4	5 565	\$39.9	* ***	460	* 554	***	956.0	\$3.0	959.9	\$3.9	939.9	959.9	139.9	***	**	\$30.0	199.9	***	99.3	499.9	***	110.0	· • •						22.0	2	33 .9	1	***	3	***		20.0
	1 104		100.0	776.7	326.1	327.0	329 1	336.7	332.9	335.2	135.9	337.0	71.	244.3	246.2	352.9	355 +	356 2	366.4	363.0	347.7	369.3	371.6	373.3	376.4	378.6	382.5	365.	390.1	393.8	397.3	#61 J				7.5.5	B. D. T.	417.5	421.4	425.4	429.7	435.2	4.274	451.2	7.75	4.664
	*****	7.566	- 11	lu T	M 71	k +-	M T-	-3 3	, , , , , , , , , , , , , , , , , , ,	9	7 7		'n	- (*	~	-	*	•	17 17	ų,	9.0	•	• •	•	♥.	- ~	4.	9.5	4.7	P+ W	- t	Ď,	•	• •	- (P	٠٠		٠. ت	+ , -	*.	ır.	4.4	4.0	• ·
1 8	4 COR	, .) •	- 00	=	- :	5 9-		10.2	e .	3 0	. ·	3	- !		7. 1.	12.4	.2.	12.8	12.4	- 1	7.1	•	13.3	* *:	7.5	13.2	13.7	13.4	. W.	ŗ	e i	*	- (•	n c	•	,	٧.٧	9.	• •	P	H. 0.	11.3		¥.
4781. 1935 CAT	SPEED	736/4	. 4	,	4	- 2	E 11	• •	n -	9	•	-	9	-		- T	• .	13 6	13.7	13	12.5	12.6	13.2	6.4.	•	-3.¢	13.0	- 9-	17.9	17 5	• •	• !	• •	, ,			*	-	- S	m ±	5.2	6.61	13 3	D	12.3	-
-	613	3		267.5	296 2	292 7	292.5	205.3	261 9	278 5	276.5	273 9	267.5	266 3	722.	25%.8	251.5	250 -	248 7	247 1	248.1	243.4	242.5	243.6	245	245.7	248.7	236.5	235.3	244.7	256.5	249.9			A . C . C		613.1	214.7	215.2	216	221.5	227.5	236.3	236.0	444.1	249 2
	DEW PT	<u>.</u>		* *	93 9	* \$	\$	2	2	\$:	× ×	\$ \$ \$	2	2		2	\$	*	\$	2	2	2	*	*	*	2	ĭ	2.3	2	*	600			i i		. 1	2	2	2	2	e. \$	\$	\$.5	2	2	2
	1634	, r	-36	-87 7	1.45-	5.65-	6	-59,4	-29.	-29.0	A	7. 7.	# · · · · · · · · · · · · · · · · · · ·	M .		-36.	-10	-26.1	-58.2	-58 2	-57.4	- *	+ . O.D.	-39.1	-39.	-39.6	-59.3	-59.3	7.06 -	1.00	-36.1			101.9		7 6 8		6.9	-	S. 99-	6.9	-60.3	-59.1	-37.7	- 186-	● · ^ ₽ ·
	£ 4		200	237 6	232.0	226	221	216.0	22.	5.66	200		- 1	90	20	9.221	173	168.	1	• • •	155.	131.	147.	143.0	139.4	- 22	131.6	128	124.	124.4	17.0									2	r T	9 5.	3.	2	73,6	1 . 1
	ME1CH1		27.5	16697.	11831.3	1125.7	11225.0	11478.9	11623 3	222		2007		12418.5		12721.4	2867.2	12050.	13201.	13357.2	13557.5	13722.4	17691	~ 33	14242.6	14425.4	14613.7	- 27.7	1.9561	1 2 5	15323 7	2042.9	17176			, , ,				27.27	17325.3	- 446	17782.0	10025.5	18279.4	
	CMTCT	*	9.26	9.5	**	100	101	102.0		•				2			=	- 5	113	• • •		116.0	117.		- 61	120.0	121.0	. 22	123.0	124.0	125.0	120		• • • • • • • • • • • • • • • • • • • •				. 22			135.4	- % - %	137.4	• • • • • • • • • • • • • • • • • • •	9.65	
	1136		37.9	36.3	30 .	39.3	90					,,		•		:		45.2	4 0.0	*	3	47.3	47.9	Š,	-	10.7		3	* 5	25.	25				•		ķ		0.70	2	,	33.6		6.		62.4

• BY SPEED NEAMS ELEVATION ANGLE BETWEEN 6 AND 16 DEG • BY TEMP NEAMS TEMPERATURE OF TIME NAVE BEEN INTEAPOLATED •• BY SPEED NEAMS ELEVATION ANGLE LESS THAN 6 DEG

	•	22	8	Š	g	g	Ž	7	į	3	į	ĭ	3	İ	į	8	8	S	8	8	ä	3	3	3	į
	156 13.	PARCE KA	29.9	21.2	21.3	21.5	21.0	22.1	22.3	22.7	22.9	22.9	22.7	22.9	22.7	22	22.	21.4	20.6	19.0	9.91	17.6	16.5	15,2	135.0
	ï	ž 5	***	133.9	?	6.863		130.0	***	939.9	***	939.9	***	***	***	935.9	***	***	****		***	•	***		***
		2 A 10	*:	*	*.*	2.0		2	.	2	2.0	2	2.3	*	2	2.3	2	2.0	2.	2.3	ī	2	2		2:
		E P01 +	****	419.9	130.0	420.0	***	999.9	939.9	***	20.0	419.0	919.9	\$39.9	99.0	999.9	\$39.9	***	139.9	939.9	99.9	***	***	445.9	22 :0
		F01 F6 x	466.5	474.8	479.0	4.23.4	4.9.	436.9	501.0	2.5	518.0	525.4	533.1	545.1	553.9	567.6	563.5	596.2	611.2	632.1	6.48.9	679.2	711.1	784.4	
		V COMP	+	4.	- .	4.4	4.4	1)	t. 4	2.4	r.	Ċ.	1.7	7	B. 9-	7	4.6-	• •	-6.2	-9.7	-12.0	-7.2	8. - -	• •	2
CALIF	1981 1	C COMP	• .	- '	n.	- 7	9 .6	•	n	.		-2.4	-2.6		-2.0	-3.7	9.4-	-7.	-0.7	-6.9	. O.	•	• •	9.E-	1
STATION NO.	APR 11.	SPEED H/SEC	• .	9.5	₩.4	'n	e.	M.	• •	8 7	8,3	Ť.	- P.	m	9	9.	7.7	9.	10 7	12.4	13.2	•	11.2	•	\$
STA WHEEL	•	# 3 # 3	238.8	216.2	- 22 .	4.66	217.0	224.4	228.7	244.7	261.6	- *	122.3	276.6	17.2	42.3	53.1	49.5	2	45.7	24 5	39.	29.7	27.9	945.9
		06 C	*	\$	\$	2.0	6	\$.0	•	6.64	o 66	\$	4.0	\$ 66	• • •	\$	6.0	*	*	• \$	4.0	43.0	1	6.0	2
		16.00 00.00	-56.9	-55.9	-55.9	- 36 7	-26.6	-56.4	9.35	-57.4	-36.7	-56.7	7.96	-56.1	-58.7	-23.8	-53.2	-54.6	-53.3	-50.6	-50.9	-48.2	-47.8	· · · ·	M. 14-
		ž i	9	9	63.	• .	58.9	35.6	53.0	50.0	40.0	4 3.	43.0	40.0	30.0	3, 98	33.6	9.18	30°.	26 0	24.0	21.0	• .	16.0	13.0
		# 15 E	10727.7	19014.2	19213.0	19522.9	19737.9	20075.0	20310.1	21679.0	20937.4	21346.5	21635.4	22694.5	22420.9	22766.7	23326.6	23720.1	24361.5	24861.7	25383.2	26257.0	27274.6	28662.5	29471.3
		CMTCT	141.0	142	# 'A#	• •	145	*	147.0	746	149.0	150	131.	152.0	153.0	154.0	155.0	. 36.	157.0	150.0	- 22		161.0	162.0	163.
		# <u>#</u>	. W	e,	9.	4.0	n.	7.1		٨.	7.6	•	5.5	٠, د	9.	•	9.9	• •	M,	•	-	•	•	7.3	4.7

•	
_	u
	=
	_
	⋖
	C.
\simeq	
ž	-
3	•
7	₹
-	-
•	T,
_	o
-	EMAC
	Ŧ
•	•
-	w

CNTCT HEIGHT GPH 19 1 1366.0 20.0 1476 6		,		•	1541 GNT						145	5 13
1366 1476 1476						_						
1366	PRES TES	200	DE P P T	9 1 8 20	SPEED M/SFC	U COMP	V COMP N/SFC	907 7 7	E POT T	MX RTO CM/KG	¥.5	RINGE
1476	₩.298	9	00 PM	60.0		-3.6	-2	293.9	309.6	39.50	20.0	9
1000	956 0	D	8	4.06	n +	B. 4-	•	2.88.7	314.7	¥,b	47.8	.1 283.
1363	945.0	13 3	0 9-	91.0			- .	300.6	307.8	64 65	ø. <u>-</u> 7	
1685	635.0	12.7	69 · 69	86 4			*	361.6	307.9	*	*	
_	825.0	12 3	₹.6-	4 00		9 ~-		301.6	308.3	m (V	\$ 0.0	•
1896	814 ○	٧	30. 00-	1 00 1		 		362 4	369.3		28.4	
2001	604.0	11.4	M	114.6		6.7	m, M	305.8	316.3	e e	24. J	
2106	754.0	n,	5.6	117.5		E . Z-	9 ,	361.9	369.0	4.	25.7	
2211	784.0	B, 9	-7 fb	117.4		-7.5		302.6	316.6	. .	26 9	
2317	774.0	₹.	9 2-	116.2		♥. 69 1	-	303.6	311.0	7 . 7	36.7	
2424	764 0	M M	-7 8	116.0		♦ .6−	4.	362.9	3.1.	œ.	33.1	
25.3%	24.5	† · 9	-7.6	2.4.1		.6-	4.	363.1	2.1.5	ø.	35.7	
2642	744.0	₩.	-8 2	111 7		-10.4	4	302.6	310.7	8 .	36.2	
2752	734.0	*	9 /-	104.6	P) -	9 0 1-	œ. M	363.0	311.5	G.	 -	
2863	724.0	٨. ٩	391	110.2	39	-11.	-	362.7	311.1	æ.	• . •	
2976	714.0	•	#) 60	114.2	9	9.01-	3 0.	362.8	311.1	8	76.0	
3078	705.0	•	- 6.7	116 1		E'01-		302.9	311.1	8.8	40.7	
_	695.0	-:	Ø 39	116.2	iņ. I	-16.3	- -	303.0	311.3	æ. Æ	8. IS	
3297	686 0	-1 2	87 64	120.0	11.2	-9.7	9.6	302.4	310.3	2.7	54.0	
3413	676.0	-1.7	-22 1	136.3	40.	6.7-	6 .4	363.7	306.7	•.	19.2	
3520	0 294		-24 1		ď.	ŋ · 9 -	*	304.6	307.2	•	16.3	4.0
3640	657.0	-2.8	-24.5	145.9	Ġ.	5.5	7.6	302.6	308.2	•	- · •	
3750.	648.0	-2.2	-24.5	152.7	9 .	M. 4-	*	306.8	309.4	•	÷.	
_	639.0	. P	-25.7	134.9	0.0	4.4.	9.0	306.8	309.5	۲.	15.6	
3973	630.0	-3.7	-25.7	4.46.	¥.0	10 7	*	307.5	309.9	٠.	9 -	
4699	9300	6.41	-26.4	153 6	0	-4.7	* .	307.5	369.0	۲.	9.91	
_	611.0	9.9-	-27.1	154.0	- 0	+ . + .	<u>-</u>	367.6	309.0	ŗ	• •	
_	602.0	-7.0	-27.8	156.6	6	-3.7	6 0	307.7	309.0	•	17.1	
4447	593.0	-7.9	-29.0	162.1	6.3	, .	ν.	366.0	309.9	÷	16.3	
_	584.0	9.8-	-30.0	169 B	4 . 9	 -	M .	308.5	J10.3	'n,	18.7	
4686	575.0	6.8	-29.8	9.001	.	•	4	600	4.	•	9	
4194	567.0	0.01	-36 7	Q.		•	60	300.6		ų.	9	
4917	556.0	-10.6	4.16-	186.3	W.	ij	M M	310.0	31.4.6	'n	7.9	
5642	349.0	-12.0	-32.3	187.2	u u	ņ	ei ei	310.1	311.6	'n	16.4	
5154	541.0	-12.2	-32.6	192.1	£.3	'n	ς.	9	312.6	'n	+ . 9 .	
5262	532.0	-12.9	-32.6	207.5	~	<u>-</u>	.	311.7	313.2	w.	17.3	
5397	524.0	-14.9	-33.3	221.1	2.7	*	•	311.9	W. W. W	•	17.6	
5529	513.0	14.6	-33.6	223.5	8	9.1	۲.	312.6	314.0	₹.	17.6	
5647	507.0	-16.	-34.8	224.2	Α. (A	7.7	8	312.3	313.6	•	17.9	
2926	499.0	-16.4	-35.6	217.6	4.		•	313.2	314.5	*.	17.2	
2000	491.0	-17.7	-37.0	194.2	M		N	313.2	114.H	ņ	16.8	
104	483.0	3	-36.9	1.001		9	o,	314.0	315,1	Α.	17.5	
6135	475.0	M	-36.2	166.6	~		~	314.1	418.4	•	20.6	
6261	467.0	-20.5	100	166.7		9	•.	314.1	318.7	ب	\$	
	440	7 10-	- 4	174.7		-		314.4	318	•		

* BY SPEED MEANS ELEVATION ANGLE BETWEEN 6 AND 10 DEG * BY TEMP MEANS TEMPERATURE OR 11ME MAYE GEEN INTERPOLATED ** BY SPEED MEANA ELEVATION ANGLE LESS THOM & DEG

The second second

•	CAL IF
Ë	_:
X	Ť
Ξ	EHACE
₩	×

一 のをう 一 かんなん かんしん

;

	•	¥ 8	318	316	318	H	=	Ë	316	2	9	5		5			-					3	=	=======================================	=	-		3	7	223	Ę	à			Ž	387	•	2	%	2	£ :	£;	ā
	ij	3 55	•		•	•	•	÷.						in i	ņ		n i							*.	r,	8				4.4	•	,	e i	•	7	2	7.	7.7	9	2.7		N I	n M
	5	•																																	_								_
		ΞŞ	31.3	77	33.7	2	32.2	32.	23.	7.	*	10 m	23.0	77.7	N.		R	P				•	2		?	•				•	•	-			•	•		•	23.0	Î	•		ž
		MX RTO	•	₹.	•	•	ņ	7	ij	ij	Ģ	ú.	ķ	ú	ú.	-	-	-:		1			2	:	*	• •	• •			2		: :		? ?		2	*	:	2		•	P.	1
		E P01 1	318.7	316.1	316.0	213.6	1,6.2	314.1	7.4.	3.6.5	317.1	216.7	216.9	216.4	9.912	F. 61.0	21.5	210.4							¥3.		6.6			***	399.9	•	•				***	\$30.0	110.0	33.0	999.9	12.0	•
		P34 7	314.2	314.7	314.6	4.4.6	315.1	315.1	7.8.1	318.6	216.2	9.00	216.2	116.1	7.6.2	*	316.7		2.7.6			217.	216.1	310.0	216.9	419.0	320.3	121	722.0	323.3	323.3	324.2	125.2	7.020	227	229.9	321.0	33 %. 2	376.1	9.74.8	327.0		* 776
		7 COMP	-		• • •	4.1-	-1.7	-1.2	•	ri i	ú.	٠,	•	•	•	•	٠	Ņ.				•	•	• -	•	4	, i	7.			-4.5	0 · P ·	M .	•			-7.	* . -	*	•		P.	•
TEMACHAFI, CALIF	<u>*</u>	U COMP	-		•	۰	ID -	- i		• .	 -	•	۲.	•	ı,	ij.	, ,	•				•	-	•	8.0		r i	, i		•		4.2	- (N 1		**	12.7	1.1	1.1	12.2		- M-	•
	1541 1541 CAT	SPEED M/SEC	~			-			4.4	6 .	*. -	.	•	•	œ,	•		+ (• ·			M	7	8	2.8	, .	•	- ,		•	<u>-</u>	•	•				13.1	5.1	-:	12.2	13.1	- 7	
	•	- 3 - 3	129.4	76.3	20 6	341 2	318.0	3000	2.682	277.4	261 9	233	530 6	225 4	6.9	8 612	237.7	260.6	200.	7.2.7		717	7.4.4	314.3	312.8	M M	307.1	*		296.	294.9	292 4	200.1	582	2 6 4 5	286.7	201 9	277.3	271.6	272.	274.5	273.8	
		DEW PT	- M	4.00	-36 3	-37 7	-36 7	9.62-	9 94-	**	\$ -	- 44-	- **-	1.84-	-46.2		9	7 64-	•					1	**	120	Ø.			2	99.9	*2.4	2	•				99.9	***	99.9	40 4	•	,
		TEMP DC C	-22	-23 7	100	-26 3	-27.1	-28.3	-29 8	E 08-	-31.1	-32.5	-33.6	-34.8	-36.1	-37.3	# 0F-	-39.6	-48.7				4.99-	-47.5	-48.5	+49.4	-36.	7		-53.5	-54.9	-38.6	*	-10		6.00	-59.1	-59.6	63-	-66.2	6.09-	-60.7	•
		7 16 26	432.0	444	436 8	429.0	421.8	4:40	467.6	400	353 0	386.0	375.6	372.6	90	3 925	321.6	9 5 6	336.0	252	7.07.	7 7 7	90	300,0	294.0	287.0	202.0	273.6		255	253.0	248.0	242.0	237.8	. 200	221.0	216.0	211.	206 0	201.0	157.0	192.	
		HE ICHT	636. 6	6632.3	6.292.9	6003.2		7 4517		7380.4	7516.6	7637.8	7766.6	7897.1	8629.3	8163.5	6599.6	8-14-8	6557.7	20.0			9226.3	٠.		9649.	9764	1928		10316.0	7.331	1 6593.7	10749.5		-	1.32.		11611.5	11761.6	11915.2	12046.4	12200.3	
		CMTCT	3		3	67.0	•	69.8	76.0	71 6	72 6	73 0	• •	75.0	76.6	77		7.0	•			2	9 9		67.0	:	•	3 · ·	. \$	97.	Z		*	44		100		10%	103.0		.2	• •	
		# #				**	9.6	20.3	20.7	21.2	21.6	22.0	22.4	22.9	23.4	23.9	7	24 · •	2	P. 1		7 7 7	27.9	7.	20.9	3	29.0	M (12.3	32.0	23.3				38.9	2	37.	37.5	9 . 9	36.5	:

145 13.	15		•		. 9	6.7	7.1	7.6	-	6 .7	e e	•	•	- (· N					16.0	16.8	16.9	17.4	• •			20.5	21.1	• •	- i			5		*	Ä	. 7	Z	<u>.</u>	į	į
-	¥\$				•	***	1	÷	33:	•	•	•									3	•	2	•	2	Ė			*	:					•	•	3		•	ř.		İ
	AK ATO	2			2	*	2	:	.	2	2	2	2	•		P. C			1		2	2	?	•	: :		:1	•	:	?	: :	8				2	:	2	: :	: :		?
	# 8 %	99.0			•	***	*	£	***	•	•											*	3	•	•			•	•	1				•	•	2		\$				
	5 %			,	762.2	X8.5	269.2	77.	273.2	27.0	2			Ž	Ē					412.7	412.9	418.8	419.7	124.0	200		1		6.29	168.4	3		į				\$12.0	1 .7	£3.	N . 9		Ř
	V COMP		• •		4	8	•	•	<u>•</u>	-	٠.٠	4.7									4.4	•.•	•:	P	9 · N	•			•	M. T		•	P (7.7		2.5			P.	D	ř
Ĕ	C COMP	13.6	•	. 4		12.5	7.11	7. =	12.6	14.7	. . .	7.9	- 1	H. 4.	0.0	17.						•	•	-		- 7	2	•	14.0	•: :	ø.	r.				•		3.6	-2.2	۸. T	ņ	:
<u> </u>	STED N/MED			-	*.	5.2	12.5	•	13.6	17.3	9 .	-	16.7	76.3						4.4	13.1	12.9	13.9	4.6	14.0				9.91	12.3	9.9	- 1	•	•		7.0	•	W. W	- .	4	e,	•
•	<u>.</u> 2	252.0		257	253.2	247.2	239.7	274.2	274.2	236.1	241.8	241.7	*	241.6	239.4	242.8		7.17		248.8	232.0	220.4	210.9	210.0	9.94	226.1		224	240.7	249.4	242.7	218.6			200.3	214.0	244.6	253.4	- *	+ · ·	123.0	•
	20 20 20 20 20 20 20 20 20 20 20 20 20 2	2	1			2	3.	2	\$	2	2	•	2	•	r i	r i	Ė	: 1		2	2	*	3	•	S.				2	.	*	e e	Š			•	2	3	\$	\$: :	?
	100 100 100 100 100 100 100 100 100 100	8.	- 2	-57.7	-	-38.	-37.7	-57.9	•. \$	-23.1		3	2						į	3	-61.2	•. =	9 , 19	6.9	•	-	R	-57.7	2	27.4	7				*	-57.4	-57.1	•	*	3	-97.1	
	į	170.			16.	- 36	152.	÷.	• . • •	1	137.0	- 77	120		723						*	3 .	. 2	2	2	5			2	3	67.0	3			3	-	13.	*		• · ·	2	•
	# 8 8 8 8	12673.2		12181.0	12348.9	- 12 B	13669.2	13837.4	14653.0	14141.9	14728.9	- 122	478.0	14090.2	2000					8.023	16427.2		16620.1	17026.2	7230.4	17660.2			18382.9	10712.6	- 98	19061			20174.5	20E24.	20705.2	21.500.2	21471.1	21917.7		N. 1987.
	carter	3			- 7		118.	116.0	117.0	1.0.	129.0	- 56 -	- 181		. 22						130.0	131.	- XZ :	R		R		Ą		• • • •	141.0	142.0			*	147.	-	•••••••••••••••••••••••••••••••••••••••	180.0) -
	TINE NEW YORK	*			3	÷.	42.8	-	Ţ	7	?	*									3	1 1.2	.	Z	.	Ë	i e	6	3	2.5	3				1	1	3	2.1	67.7	3	S	

BY TENE MEANS TENETHAN MARKET BETWEEN BEEN THEORY OF THE PARTY OF THE MARKET BEEN THY TRAPOLATED BY THE PARTY OF THE MARKET BEEN THY TRAPOLATED BY THE PARTY OF T

	•	22	ż	Ė	ż	ż		ż	ż	į	ij	Ė
		Ī	4.2	2	23.0	2	£1.3	20.0	•	-14.0		:
	ā	ξĒ			:	•	•	•	•	:	:	•
		# # # # # # # # # # # # # # # # # # #	2:0	2	2	2	2	2	•	2	?	?
		# 5 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	***	•	23.			•	•	•	•	***
		52 52	874.6	•	24	617.1	£. ¥.	-	3	7.2.2	766.8	7. 2.
		* COS	•	7	7	-7.7	-7.7	•••	•	-78.	*.	2
CAL 1F	į	- COM	*	7	- •	-7.S	۳. ۲	8. B.	•	P	-3.8	.
STATION NO. TEMACHAPI,	## IF 194	4 7 EE	•	7.7	- - -	10.7	12.0	=		13.6	•	3.
Ē	•	6 0 6 0	*	# *	14.	42.9	30.1	2	¥. IR	23.0	7.	•
		2 2 2 3	3.	2	2	2.3	•	2	*	:	\$	2 .0
		2 % 5 0	-62.9	134.6	-4	-53.8	9.18-	-7	-44	-47.3	-42.8	-45.4
		2 2	2	2	30.0	27.8	22	2 2.	20.0	. 2	13.0	13.
		HE SET	22984.0	23475.9	23913.5	24550.4	25667.7	2007		27618.7	20 TES	27410.8
		CONTCT	- 1	- 88 -	. 3	187.0		- 2	• • •	• • • • •	162.0	
		T.	2.5		74.4	, <u> </u>	77.8		•			•

~	CALIF
٠,	ш
0	3
ž	ICCE
_	=
Ŧ	år.
3	_
ij.	OL .
-	▥
Œ	_
ř	ũ
ø	EELEP RI

14 APRIL 1981 1815 GMT

2

.

10 10 10 10 10 10 10 10	CMICI		2	T C		7 .	27.5		ALCO A	2	E P01 1	X TO	Į	RANCE	7
10 10 10 10 10 10 10 10		3	ŧ	ပ ၁		2	M/5EC	M/SEC	H/SEC	× 2	×	CI/KC	P C1	Ē	2
2		168.0	1002.0	22.6	9.0	330.0	'n	ņ	•	295.6	313.7	6.7		•	•
26.1 9 99 9 1 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2	•	- 34 .	**************************************	21.4	8	286.7	er,	*	-	294.6	312.	*	45	•	7
15.5. 1	•	201.0	989. r	20.3	٨. ٨	283.3	۲.	•	2,1	294.4	312.	4	1	•	. 4
943.4 980.0 17.7 9 9.7 22.7 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0	•	360.5	979.	19.2	9	280.9	•		1	294.1	311.0	17			y
10 10 10 10 10 10 10 10	•	465.4	0.096	17.9	D	267 5	9.1	6,	M. I	293.8	309.9	•	1	-	-
751.2	•	563.1	957.0	17.1	S	251.7	۲.	49	m. 1	293.9	310.2	•	47.2	-	26
751. 9 254. 1	• ~	652.6	947.0	16.3	9.4	257.8	ņ	ď	•	294.	309.2	9.6	**	-	101
942.9 926.0 14.9 4.0 19.0 4.0	•	751.0	936.0	15.4	4.	198.2	•	ď	٠	234.	309.1	en en	47.0	-	3
121 3 996	•	45.9	926.0	13.0	4	169.6	m	-:	m.	294.6	310.5	-		•	3
12.5 906. 14.3 4.2 122. 1.2	•	934.8	916.0	• •	4	92.7	ď	1	•	295	10 . D	4		•	3
12 13 13 15 15 15 15 15 15	•	1027.6	906.0	14.H	4	122.1	*	·	-	295.6	311.2		20.7	•	•
12.1 2. 2. 2. 2. 2. 2. 2	9	1121.3	9.96	9.8	F	9.5	0	*		206	7117	. ~			
1980 1980		1215	8	er e	M	7.7				7 700	- 612			: -	:
1817 1855 1856 1856 1856 1857	9	6 1021	82.0		9 0							•		- •	0
1977 1975 19	•				•	2 4		· 1	•	?!		.	0.0	Ņ	
1567.7 8450. 15.6 - 1.6 7 134 5 8.0 - 5.7 85 802. 8 10		1414.0		0	, N	34.8		٠ . د	*	701	210.4	'n	4.7	·	22
1666, 7 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	•	1517.1	822.0	9.0	- 9	-34 %	9	-5.7	9.	362.0	9. 9. 9.	 	20. 0.	♥.	į
1986. 13.9 -7.5 133.4 7.8 -5.7 5.1. 382.1 389.7 2.6 21.9 1910.2 816.0 13.9 -7.7 129.0 7.8 -5.5 7 5.1. 382.1 389.7 2.6 21.9 1910.2 816.0 12.3 1.7 6 129.0 7.8 -6.4 5.1 382.1 389.7 2.6 22.9 1910.2 816.0 12.3 1.7 7 766.0 11.9 -7.7 129.0 7.8 -6.4 5.1 382.2 3111.1 2.7 2.6 2.8 2.8 2.8 2.8 2.8 2.8 2.8 2.8 2.8 2.8	•	7.88.7	976	• •	-7.3	134.9	m. 0	9.0	ø,	302.1	309.0	5.6	20.0	•	331.
1988.2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	M	1717.1	036.0	13.9	-7.5	133.4	8	-5.7	'n	302.1	309.7	5.6	21.9	•	327.
2222.7. 736.6 6 6 6 1 1 2 3 1 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1	•	1608.2	0.920	13.1	-7.6	131.3	m ;	n e	4.	302.3	310.0	2.6	22.9	•	124
2217.7.7.7.7.7.00.0.0.0.0.0.0.0.0.0.0.0.0.	0.5	1910.3	816.0	12.3	-7 7	129.0	4.	-	•	302.6	316.3		22.	-	25.0
2222 7 706.0 9.0 10.4 125.7 10.4 125.7 10.4 125.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10		2013.5	806.0	6.1.	-7.6	128 5	. 00	9-	•	302.2	311.1		24.8		2
2222 7 706 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		2117.7	796.0	4	G	127.7		4		100.7			. 40		
2328.7 776.0 8.8 -6.3 125.4 8.7 -7.1 5.0 303.1 310.9 2.6 28.9 7.25.2 2228.7 776.0 8.8 -6.3 125.4 310.2 2238.7 776.0 8.8 -6.3 125.3 4.8 6.7 -7.0 303.1 310.2 2.8 29.7 2.8 2238.7 776.0 5.9 -9.6 127.3 9.3 -7.4 5.6 203.4 310.2 2.8 29.7 2.8 21.8 22.4 22.4 22.2 22.3 21.8 2.8 2.8 22.4 22.4 22.4 22.4 22.4 22.4	•	2222 7	786.0		4	0	ď	9		362			27.		
2241.0 747.0 7.3		2328.7	276.0	ď	4	4 60	ď			101			90	•	
2242.1 747.0 5.9 -9.6 127.3 9.1 -7.3 5.4 203.4 311.7 2.7 311.7 311.7 2.7 311.7 2.7 311.7 2.7 311.7 2.7 311.7 2.7 311.7 2.7 311		2425.0	7.47	V	•	26.8	, N			100					
2642.1 747.0 5.9 -9.6 127.3 9.3 -7.4 5.6 203.4 310.7 22.8 31.0 22.4 1.2 732.0 4.7 110.8 128.5 9.0 1.7 1.0 5.0 3.4 310.7 22.8 310.7 1.0 22.8 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0	•	2533.0	237.0	M	. 60	126.8	•	-7		7.191	111.7				
2741.2 730.0 3.9 -11.5 132.4 6.4 -6.2 6.7 133.4 1369.5 2.3 31.5 132.4 6.4 -6.2 6.7 133.4 1369.5 2.3 31.5 132.4 6.4 -6.2 6.7 133.4 1369.5 2.3 31.5 132.4 6.4 146.9 9.6 17.5 132.4 6.4 146.9 9.6 17.5 132.4 1369.4 2.3 31.5 13.5 13.5 13.5 13.5 13.5 13.5 13	•	2442	247		9 0						7 4 7				
2552.2. 728.0 3.9 111.5 132.4 8.4 15.5 132.4 132.4 8.4 15.5 132.4	•	2741 2			0 0	9 000	9 6					n r	•	•	•
2551.1. 710.0 3.0 -1-2.0 140.0 8.7 -15.0 140.0 3.0 -1-2.0 3.0 -1-2.0	•								· ·			•		, .	
100 100	•	2001) P			P 0							•	
1274 691.0 1.4 1.6 0	•			· •								•		•	•
1274.1 691.0 1.4 -16.0 160.6 9.9 -13.3 9.3 9.3 124.1 12.2 12.2 12.2 12.3 9.3 12.4 12.2 12.2 12.2 12.2 12.2 12.2 12.2	•	1160					٠. م		•			•		•	
1337 9 6 6 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		1274	3 107					,	•			•		•	
Market M	•	4 4 4 4		-		9.67		7	•			• •	Ç.	- 1	
March Marc	•			: *		7			•			•		•	
17.00	•			•								•			
201.0 1 201.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0	•			- •	. 77	- 60	y .					ŗ		•	
10.00 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	•		.00	7		0.70	n		•	2	200	Ċ	-	•	
4244.4 647.4 14.1 120.4 146.6 4.4 11.7 14.9 140.14 1409.7 14 140.9	•	2019		2 2	9 72-	29.	•	•		307.1	2.4	•	9.0	•	
4004.0 620.0 14,0 126.2 149.3 4.3 12.2 3.7 307.0 309.0 77 155.0 31.4 12.2 3.7 307.0 309.0 77 155.0 31.4 12.5 3.7 307.0 310.0 77 155.0 31.4 12.5 3.7 307.0 31.0 77 155.0 31.4 12.5 3.7 307.0 31.0 77 155.0 31.0 12.4 12.0 31.4 31.0 77 155.0 31.0 31.0 12.4 12.0 31.4 31.0 77 155.0 31.0 31.0 12.4 31.0 31.0 77 155.0 31.0 31.0 77 155.0 31.0 31.0 77 155.0 31.0 31.0 77 155.0 31.0 31.0 77 155.0 31.0 31.0 31.0 31.0 31.0 31.0 31.0 31	•	3924.3	637.		-25.3	156.6	m. •	-1.7	6. H	207.3	7.60	÷	4.0	e.	ž
4149-10 619-6 -4-8 -26-8 147-4 4-7 -2-15 4-6 207-9 2010-1 -7 18-8 8-12 4-6 207-9 2010-1 -7 18-8 8-12 4-6 4-6 208-9 8-12 207-1 157-1	•	4636.0	620.0	• •	-26.2	149.3	₩, +		N. 19	307.5	76. 76.	۲.	18.	- m	ğ
4266.6 610.0 -5.1 -27.1 153.1 5.4 4.6 366.6 311.6 .7 15.9 5.4 4.6 366.6 311.6 .7 15.9 5.4 4.6 366.6 311.6 .7 15.9 5.5 5.6 5.0 -1.9 5.7 156.6 5.0 -1.9 5.7 156.6 5.0 -1.2 5.7 156.6 5.0 -1.2 5.7 156.6 5.0 -1.2 5.7 156.7 156.7 5.7 156.7 156.7 5.7 156.7 156.7 5.7 156.7 5.7 156.7 5.7 156.7 5.7 156.7 156.7 5.7 156.7 5.7 156.7 5.7 156.7 156.7 5.7 156.7 5.7 156.7 5.7 156.7 5.7 156.7	•	4154.5	619.0	• •	-26.8	147.4	4.7	-2.5	•	307.0	316.1	ŗ	18.	4.2	22
4382.2 601.0 -5.5 -27.4 161.5 6.6 -1.9 5.7 309.6 311.6 .7 15.0 5.8 4.5 4.6 4.6 4.6 4.6 4.6 4.6 4.6 4.6 4.6 4.6	•	4265.6	610.0	-5.1	-27.1	130.1	ų.	-2.4	•	186.	311.0	٠.	- 5. - 5.	ų,	722
4880.4 592.6 -6.1 -27.5 160.6 6.0 -1.2 5.0 310.2 312.4 .7 16.4 5.7	•	4382.2	6.1.0	10.00	-27.4	1.0	9	6.51	5.7	309.6	311.0		18.6	10	122
	•	4888	200	4	-27	7 87	4		•	416	212		*		22
	•				•		•								

• BY SPEED MEANS ELEVATION ANGLE BETWEEN 6 AND 10 DEC • BY TEMP MEANS TEMPERATURE OR TIME MAYE BEEN INTERPOLATED •• BY SPEED MEANS ELEVATION ANGLE LESS THAN 6 DEC

					STS CHEEL	STATION NO. UMEELER RIDGE,	2. CALIF							
					±	APRIL 1615 CHT	•					-	160 12	.:
CMTCT	HE I CHT	7 E	76.74 0.00	06 c	6 1 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	SPEED M/SEC	U COMP	* COMP	P0T T	E POT T	MX RTO	# to	RANGE	
9	4727.8	575.0	-7.6	-20.1	186.9	•	٠	4.	311.1	313.2	٠	17.4	'n	-
52.	4936.8	567.0	6.2-	-28.2	199.7	7	•	•	312.0	1.4.1	Ņ	17.6	•	_
53.0	4960.9	558.0	8 .8	-28.9	506.6	1	0		312.4	314.4	٠	17.7	•	_
9	5072.7	330	4.00	-29.4	200.8	6 ,		4	7.7	4.0.	٠	17.7	•	_
20	5183.7	342.0	* ·	-30.5	208.4	e .	, A	*	7.77	. n. n	ė	17.7	-	_
9 1	5314.3	533.0	-11.7	-30.6	202	4 •		M (3.0	6. T	•	6 .		
/ 0	3429.9	953		2.15	M . M . M	m •		4 1		MIA.	ń.	9.6		-
		0.00		- 26		• •	•	• •		214.7	ņ.			•
	4784			2 4 5 . 6	- 400	. 4	•				ų, s	• •		• •
				13.6	N 76-	• • • •	•	- 11 • F			· ·			•
62.0	6028.5	463	-17.8	-35,5	186.6	M	m		314.1	7.8	۲,			
63.0	6152.0	477.	10.0	-33 9	104.4	· •	· ·	5.6	214.7	316.3	•	24.0	•	
3	6278.7	469.0	-19.7	-33.2	5.16.	+ .	m	n. -	314.0	316.4	ń	28.7	•	-
65.0	\$25	4 54	-21.0	-34.5	183.7	* .	•	▼ .	314.6	316.1	4	20.3	•	_
. 9	6535.2	453.8	-21.8	-35.6	192.3	-:	ņ		318.2	316.6	•	27.3	•	_
67.0	9.649.6	446.0	123.0	+ · 9E -	220.0	٠	• 1	'n.	3.5	316.4	Ť	8	•	-
•	6.10.0	436.	-24.4	47.4	255.0	ń,	i, i	'	12.	216.3	ú,	8		-
					2 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	•	•	•		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	į			
	100		- 20-	100	9 M			9 4	716					
72.	7275.9	419.0	4.67-	8.04-	301.9		•	•	314.0	7.0.5		, ,	•	
73.1	7399.0	402.0	-30°3	9.14-	226.1	•	٠	٠	315.2	316.0	ú	¥.	6 .7	
7	7541.7	394.	-31.5	-42.3	209.7	•	•	T 1	315.5	316.3	ú.	22.0	•	
۲:	7660.4	307.0	-32.3	M	223.7	e e	•	K , 1	3.5	316.8	Ġ	• ·	•	<u>.</u>
	7657	300.0	-32.9	• •	233.6	m m	n +		216.8	317.5	ui c		•	7
		366.0	-38.0	4.00	248.4	, m	, ,	•	7.7	310.0	! "		•	
79.0	1.75.1	360.0	-36.4	-47.0	256.8	M. V.	9.6	٠	317.1	317.7	Ξ.	32.	9.9	_
	9710.9	152.	-37.5	0.0	263.6	ia (Ť.	₹,	317.5	410. 0.0	-	2	•	-
				D . G	267.	- ·	- (- 1	6.7.5	2.7.5	- 6	25.0		•
7 7	27.6		7.5		7.00) I	> P1	•	216.					"
1	6633.7	327.0	6.14-	•	256.0	m	M	•	210.2	999.9	2	999.9	•	
93.	6979.9	320,0	-43.2	2	263.4	•	•	ņ	310.6	999.9	*	93.9	6.7	
2	9167.0	314.8	-44.3	2.	270.3	9.10	9.	• · •	318.7	939.9	3 .9	\$3.0	•	
97.1	9236.2	306.0	-44.9	•	266.9	•	•	₹.	319.7	6.66	•	6.66	•	
2 3	9367.4	302.0		2	256.7	, ı	. i	• •	6/6/2	129.9	•	22		
	7323.2	230.					• •	- °	326				•	• •
	200				200				72.7	600				•
	10 M	278.	7	8	261.1	- M		M	721.2	6.000	3	666	6.7	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
9.0	10035.7	272.0	-10-	•	268.4	•		ď	322.3	9.00		•	•	' _
Ž	10200.4	266,0	-52.1	2	276.1	•	. .	• •	322.0	999.9	99.9	23.9	.8	_
98.	10347.8	266.0	-53.2	***	284.3	4.4	4.6	-2.4	323.4	999.9	6 .	9.666	•	_

• BY SPEED MEANS ELEVATION ANGLE BETWEEN 6 AND 10 DEC • BY TEMP MEANS TEMPERATURE OR TIME HAVE BEEN INTERPOLATED •• BY SPEED MEANS FLEVATION ANGLE LESS THAN 6 DEG

CALIF	
STATION NO UNEELER RIDGE.	

						:		1							
							1815 CHT						•	~	٠
118	CMTCT	MIGHT	2	TEM	14 930	\$1Q	3966	U COMP	* COM	P01 1	E POT 1	MX RTO			
		•	ŧ	ت ا	ပ ၁	3	M/8EC	H/SEC	M/8EC	ž	90 80	GW/KG	FCT.	ž	12
	*	1 1472.7	255.	-34.	99.9	288.5	7.4	9 2	- 23	124.0	•	•	4	,	•
	•	2 94 50	249.0	-55.1	6 6	286 6	•	•	- M	324.5			666		•
•	K	10754.5	244.0	-35.7	6 66	287 6	M. 6		8.7-	325.5	6.666		000		2.
			236.0	7	* 55	290 2	9.3	œ •	-3 2	326.8	6.666	000	6 666		
					6	291	•	ф Ф	20 E-	327.3	4.00	6.6	6 665	•	
	2		200		F (265	*	•	4.6	326.9	995.9	Ø. 9.	* 566	•	2
-	7	11524	216		A 10	673	- 1	- 1	۲,	329.7	9.666	6 6	6 666	•	2
		11670.7	21.0	5.66		404 S	0.0	N .	* *	331.5	900	5 56	* **	•	27.
43.1	. 65	11020.7	7.0	8 65-		278.9		, v		333.5	999.9	5 56	6 60 6	,	\$
4 .7	2	11943.2	202.0	6.65	* 2.	282 9	-	9	N C	332	666	6 d	6 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4		Ä
*	107.0	12099.5	0.76	-60.7	5 56	275 0	•	9.	3	336	6.66		. 000		\$ 2
		2227.		6.0	6	260.3	•	•	-	340.3	6 666	6.66	6.666		Ä
				M .	66	251 3	-	0	9 6	343	999 9	\$.0	6 666		=
		2000		9.0	A 66	248 6) (V)	-	4	347.3	9.666	\$	9.99	•	5
7	112.	12074			, ,	8 9 9	•	9 (. 7	330.1	6.66	4	4.664	•	7
19.1	113.	13057						3 .	* 1	152.	999.9	\$	***	•	į
••••	- *:	13207.7	163.	V 201		2 - 2 - 2	, ,	::	0 4	3,40 W	999.9	6. G	Ø 666		
90.3	113.0	13362.5	• •	-57.7	5	239 7	4	. 0		47.			6 6 6 6 6 6		į
90.0	1.6.	13521.7	157.0	-56 7	66	239 6	12.6	8 0 6	4	367.5	000			:	•
T. 15	117.0	13665.	153.0	-57.4	љ 6	240.9	12.9		, m	369.	9.66				•
		- Teles	•	-57.6	6.66	241.6	75.7	11.2	•	371.6	999.9			-	•
		14824.3	143.0	-57.4	6.6	238.5	12.8	4.01	ţ. •	374.8	6.656	6.66	6.666	-	1
						233.4	n i	6.0	٠. د	377.2	6 666	3	***	2.	;
~ 75	122.	14869.3				2 2 2 2 2	•	- :	•	000	6 666	6.6	939.9	22.6	•
4.7	123.0	14761.5	129.0	96-	* 64	230.3	9 40		9 6	7	6.66	•	999.9		;
" 2 1	124.	14909.3	126.	-59.3	6.6	233.5	1.8	2.2	•	306	0 000				:
e i	125.	15111.9	122.8	7. 86	7	234 5	13 6	:	ι. Γ.	192 3	6.666	6 66	6.666		\$
57.7	27.			-27.	d	229	6 N	9 .	•	394.6	9.66	9.0	939.9	15.1	\$
57.7	126.	15652.3	112.	7.90	6 6 6	208.0	n e	- 4	- 0	n 0		6.0	99.0	5	•
7.	129.	15624.7	. 69.	-36.1	6 66	232.4		4							Ė
99.	170.	16062.0		-36.7	\$	234 0	4	6		412.3	000				
29.6	121	16248.	195.	-24.7	\$ 66	231 5	14.4	9.7		415.8	5 666				
× •	. 25		99.0	-57.4	6.6	223.0	Ē.	7 8	8 5	418	999.9				•
			*	-08.1	•	210.4	0 7	•	•	420 4	999.9	3	999.9		•
		10000	93.0	- 6P-	2	228.4	 	90	-6 5	420 8	9.666	6.56	999.9	19.2	
	76	2.24		0.00	2	223.0	•	D	: :	422 7	***	\$	930.0	19.9	•
						230.4		7	9.	426 8	***	3 .0	***	20.5	•
3	70	7.600.2				237 3	9.0	9 0	6 0 (432.6	99.0		999.9	2.	\$
3	139 0	17925.2						•	e :	916	999.9	•	99.9		÷
63.6	•	18171.2				9 1 10		9	M 1	9.74	999.9	?	999.9	22.	•
				•	:))	•		•		939.9	ŗ	939.9	22.5	•

* BY SPEED MEANS ELEVATION ANGLE BETWEEN 4 AND 10 DEG * BY TEMP MEANS TEMPERATURE OF 1:NE MAYE BEEN INTERPOLATED ** BY SPEED MEANS ELEVATION ANGLE LESS THAN 6 DEG

						STA	STATION NO.	. CALIF							
						•	## 11. 1015 GH	196.					•	12.	•
w z	CNTCT	A LANGE	ë e	7EMP 06 C	DEC P1	918 00	SPEED M/SEC	338/H	V COMP	- ¥	E POT T	AX ATO	ŧţ	PARCE NA	22
•	•	18428.3	22.0	-58.1	6 66	247.1	•	*	-	196.5	999.9	***	999.9	22.7	
-	42.	9.90	200	-36.1	\$	212 6	M .	F. 7	ø.w	*. 7.4	999.9	***	***	22.0	÷
•	143.0	10003.	67 13	-56.2	6 66	206 4	7	~ M	† .	469.9	939.9	8 .0	139.0	23.1	\$
	•	19176.	940	-56.4	6 66	206.6	P.	4	6.3	475.0	999.9	3 .3	939.9	23.5	÷
	143.0	19377.4	62.0	-56.7	**	209 0	4.4	•	•	479.4	25.9	3 :	\$3.3	23.9	÷
4	146.	1.000	39.0	-57.7	* 64	207.9	P)) M	9.0	404.	935.9	2	***	24.1	\$
•	147.	. 55 63	87.0	-36.9	6.66	213.7	₽. •	9	4. B	490.7	199.9	2	***	8. 2	1
		20251.7	*	-36.7	6 66	233.3	*	6 m	6.8	436.7	\$33.9	**	***	24.9	\$
		20494.9	52.0	-56.9	*	248.3		6.	•	563 7	939.9	\$	\$30.0	28	3
	. 36	20066.9	43.	A. 78-	6 66		ų	•	2 7	511.2	999.9	2:	22 :3	23.2	;
	151.	21131.2	47.0	-55.7	*:	96.2		- E-	m.	521.3	499.9	\$	***	3 2	į
	152.	21400.0	45.6	-56 1	9.0	147.6		•	? .	527.0	9.666	3 .0	999.9	%	3
	183.	21047.0	42.0	-98 /	99.9	26 / 9	•	•	•	530.3	999.9	\$3.0	99.9	- E	3
•		22310.0	39.	-56.6	2.3	6.5%	- ~	• •	m .	547.8	999.9	2.3	***	2	47.
•	100	22653.4	37.0	-54.8	6.66	79.1	0,0	-9.7	6.1-	560.7	999.9	S	23.3	24.5	į
•	1	23196.1	7	-24.1	6	27.9	•	- M	9.6	576.1	939.9	2.3	99.9	24.2	į
-	137.	2300A.A	75	-53.7	2	3 2.6	M .	•	• · •	587.4	939.9	3	***	23.6	į
•		24662	30.0	-50.7	•	44.0	9.	•		7.23	999.9	***	33.	22.9	\$
-	- 24	26492.1	27.	10°	•	91,1	•	-7.6	•	631.2	939.9	3	***	22.1	į
•		25125	25.		•	88. M	13.0	-10.7	4 .4-	646.5	939.9	2.0	***	20.9	₽.
m	161.0	26643.6	22.	-47.2	•		36.0	• •	-7.5	673.2	939.9	\$	3		÷
M	162	26669.9	20.0	-30.4	6.	30.2	•	1	-7.7	•	110	2.	\$35.5	•	į
•	163.	27741.4	17.	-48.7	2	353.1		-	E.	729.3	999.9	\$	***	17.0	3
	7	5.5716	14.	-4.		331	4 0 0	•	-9.5	784.3	\$50.0	2:	935.9	17.2	3
•		20102		- 16. 1			6.66		9.66	939	939.9	2		33.5	3
•			•						:						•

				STA TEH	STATION NG. TEMACHAPI, CALIF	CAL IF						
				•	APRIL 1818 CMT	ě					147	7
HE I GHT	ž E	168 06 C	DE C	# 5 0 0	SPEED M/SEC	U COMP	V COMP	100 100 100 100 100 100 100 100 100 100	6 P01 1	MX RTO GM/KG	ξţ	RANGE
1366.0	8.49	21.0	8.3	- 20 -	6.3	-3.1	4.0	306.3	321.3	S.	29.	•
1473.8	0 /50	16.8	-2.4	114.9	9	•	8	305.1	316.0	i M	23.6	
1574.0	0.44	16.7	6.5-	113.3	9 9	•••	3.6	303.9	312.5	6.8	20.8	•
1674.6	037.0	• •	6. 9	110.0	*.	₽.9-	8.5	302.0	3) 6.0	4	21.0	•
1775.9	827 0	m. m	o .	106.6	M. 9	9.9	•	302.4	309.9	2.3	21.9	•
7.7901	9.0		•	109.7	•	9	6	302.3	309.9	5.6	23.4	•
1976.3						* 1	N P	302.6	9.0	6	23.7	•
7 67 67	9 6 6				. •	n :	,	0 P	-	N (27.4	•
22.74.3	779.0		7	- 2		2	•					•
2391.0	769.0		7.	117.2		7	4	103.1	M. W.			
2400.0	759.0	7.0	•	17.0	9.0	6-	+	363.1	316.9	7	9.17	-
2597.6	749.0	.	9.6-	117.9		• •	5.2	302.9	310.0		7. 7.	-
2696.3	240.0	4.7	.	116.4	5, 11	-10.U	.	302.9	316.7	3.5	3,0	-
2867.1	730.0	Ø.	٠. •	114.	6	6.01-	•	363.1	310.0	5.6	37.9	~
2907.7	721.0	 	٠. ا	- 7	m. 	4.01-	* .	302.9	310.5	2.6	 •	.;
30.00	711.0	۲.۲	6 1	12.0	6.0		•	303.	310.7	%	43.0	~
9.	783.0	ĸ.	8 - 1	12.1	0	- 0 -	-	302.9	9. B.	5.	41.5	ä
3215.		- (9.7		• ·	•	*	101.1	N. 2	•	 	ä
1955		N T	2.12.	9.07		-6.7	n 1	2.7.7	307.4	•		m i
1444		•					:			- :		•
7.25	657		-22				- 17					
3749.0	649	-2.	-23.9	HIST.	9			300	300.4	•		
3066.6		-2.8	-24.1	197.4	m.	, M	•	307.2	269.9	•	2.5	
3972.7	631.9	-3.4	-24 6	1.091	9.1		•	307.7	4.012	•	17.5	÷
7.00	622.	• i	-23.6	164.	•	-2.4	•	307.6	700	•	17.5	•
	7 10	n (-27.0	109	•	r: -		3.705	7.0.0	٠.۱	7.9	•
7 7 6 7 7			, , ,		, ,	•				ŗ,	N. 9	•
4654						•	•		N	•		
***	579.	-2	-28			•	M			•		
4754.3	571.	•	-29.2	203.1	M	-	P	M. 0. M	312.3	•	17.2	
4077	562.4	-10.	M. 02-	206.0	M	n.	2.7	H	312.2	ņ	17.6	•
B. / B&+	924.	-10.7	- 30 · 9	266.9	. .	* :	2.0	310.0	312.5	'n.	17.	•
2000	346.	-12.0	-32.1	202.9	n	<u>*</u> :	6. E	310.6	312.1	'n	- • •	•
5226.2	937.	-12.5	-12.7	199.3	u.,	n .	e n	¥.11E	312.9	₹.	9.90	•
9340.7	529.	-18.1	-32.4	202.7	e m	۲.	in m	312.0	313.6	ņ	17.0	;
* i	521.0	- 1	6.1	269.7	o.	• •	# 1	312.2	313.7	'n.	•	•
	913.	-13.	-33.7	214.0	•	M :	M .	415.4	917.9	₹.	•	
* . ZA *	000		m. 1	220.2	• (o i	= 6 M	312.5	A. M.	•	- 6	
12.2	P. 4	*	Ŗ	228.0	P. I		n r	* 2 2 2	V.E16	•	9.6	•
1967		A	0. P. P.		n •		P 6	N. H. C.	D. + 1.0	<u>.</u> ,	0.6	
					- 1	- '	9 1	315.7	8.4.8	•	19.8	•
			?.	7.76.	N . N	·		-	1.029	•		ņ

BY SPEED MEANS ELEVATION ANGLE BETWEEN 6 AND 10 DEC BY TENP NEANS TENPERATURE OF TINE MANE BEEN INTERPOLATED . BY SPEED MEANS ELEVATION ANGLE LESS THAN 6 DEC

CAL 1F	•
STATION MO. TEHACHAPI, C	APRIL 1918 CRT
# F	-

<u>ئة</u> ر.

•	22	Š	22	Ž	i,	Ċ,	į	3	2	726	75	ž	ž	Ä	Š			į	į	Ä	Z	Ä	Ä		Ä	ż	Ž	,	į	<u>ن</u>	=	Ë	Ė	ġ:	N S	Ċ		į	į		Ş
=	3			9	,				+	•	•	•	•								4.7	4.7	4.4				•	•			+ .	4.2						•			2.5
147	- ₽Ę	28.7	.	• ·	- ·	•	: ×	ì.	× 12	R	7. R	T.	72.6	e i	e.	e i	į			•	***	3	•			***	***			•	***	?	•		Ē						
	EN RTO	•	•	Ţ	•	•	• •		!'	•	ä	ų.	ij	ù.	,	Ņ.	•	:				2.	2		2			?: \$:			2	:	2		r.	r i					2
	# 604 PC # 7	315.0	316.1	7.07	9:2:6		210.	214.2	316.5	316.4	316.6	316.5	216.9	916.6	316.7		×				***	***	400.0			939.9	139.9	6.665			***	3	200								
	- 3 - 3	313.7	314.6	214.3	314.2				315.4	318.6	315.7	25.0	316.2	215.9	1.6.1				- 6	317.3	317 7	317.4	7.0.	120		200	75.7	75	127	# T	Ž	22.5	726.2			2				7	343.7
	V COMP	•	٠.	-	• •	P •			•		۲.	~	M .	• (n.	-	•		•		•	T	.	•		•		;	•	-2.	-1.7	•.	-1.1		-2.0	7.7	•	N •) 	•	! •
· ·	U COMP	ŗ.	" .	ď.	- •	•	•	-	•	1.7	1.7	•	2	÷ :	2.9	,	•	•	• •		•	n . +	8			•	•:•		• •		m. ==	•. :	9.11	m	P) (M (0.4		:	7.
APR 11.	SPEED M/SEC	•:	•	ů.	• •	ij,	•		•	۲.	6.	2.5	. s	o i	m (· ·		•	•	M		•	ņ	e i	9	•	•:	a.	•		• :	12.0	12.	K	0.0	*	•	n •			
:	<u>=</u> 2	1.961	200.1	2%.	# · · · · · · · · · · · · · · · · · · ·	0.00	346.	100	299.2	276.4	248.9	235.9	239.2	240.4	242.6	243.0	2.00		· ·	266.9	260.1	253.0	253.5	262.4	274.	273.8	271.2	270.4	273.2	203.7	200	200.3	586	203.9	201	277.6	27.2	271.5	278.1		265.9
	DE C PT	-35.5	4.46	- 12	r R				-39.6	9.04-	4.14	-42.8	-43.5	*	• •			î		8	2	*:	*. *	? ?	22	2	2:	*			2.	\$	¥.	\$	2	? ?		r i	; ;		\$
	16.7 06.0	-21.0	-21.6	22.9	- 5		1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	M	-29.5	-30.3	-31.5	-32.7	-33.6	- 99	78.5	-37.2				- 64		-45.2	-46.3	-44		-49.6	-34.6	-51.6		6.48-	4.88-	1.96-	-57.1	-57.1	- 20	- 100		* · · · · ·			-3-
	Ęŧ		456.	451.0					• - 2	• • •	393.0	306.	379.	372.	365.		. 295			325	J. 9. 0	313.0	307.0	300		202.0	276.0	270.0			240.	242.0	237.0	232.0	226.0	221.	216.	211.	200		192.
	#E 1CM	6292.3	5420. 1	6511.3	6647.7	7.	25.75	7.55	7275.9	7399.6	7524.9	7651.8	7786.5	7910.9		2177.2	6293.			7.77	8962.7	9.000	9210.7	9271.0		9779.3	******	10062.7		1. 1000	1.679.		16697.3	11032.3	11197.7	11330.7		9.000			12223.0
	CMTCT	65.	•		9			7	2	74.0	ŗ	76.0	77		2					7	*		:	2		92.0	93.0	ï	F		7	2		•	- 25	10%.		2			•
	TIME	13.1	٠.	•	n. 9.					•	19.2	. ¥.	• •	20.3	20. 10.	21.3	21.7	7	. 22.	21.2	23.7	24.	24.5	24.9	. X	26.2	26.7	27.0	27.4		2	23.5	29.6	2	70. M	70.7	- 1	5.6	7 7 7		33.5

STOTICH NO A	TEHACHAFI. CALIF

į	į	1
. 3	_	, 3 , 3
		1
	-	
		99.9
249.7	-	*
		\$. \$
	•	
	٠	
231		
235	•	
234		
226		
226.3		6.66
22.9	•	
236	•	
	•	
	•	
	•	
226	•	
233.0	•	
	•	
215.2		
2		
7	•	
	•	
22	•	
22		
9		
217.6	•	-20.4
	٠.	
192	e	

• BY TEMP WEARS ELEVATION ANGLE BETWEEN 6 AND 10 DEG • BY TEMP WEARS TEMPERATURE OR TIME MAVE BEEN INTERPOLATED •• BY SPEED MEANS ELEVATION ANGLE LESS THAN 6 DEG

•

	•	¥ 9	5	ë.	3	8	i	\$	•		7	=	\$	•
	147 14.	RANGE	27.5	27.4	27.1	26.7	26.4	25.5	24.7	23.5	22.4	20.0	19.2	439.4
	-	¥ Lo	999.9	19.9	9.646	955.	999.9	959.9	20.0	133.3	\$39.4	999.9	939.9	6.666
		MX MTO GM/KG	2	99.9	\$.0	\$	2.0	2.2	\$2.°	2	2.0	3.5	2	
		E POT T DG K	999.9	999.9	999.9	999.9	999.9	999.9	999.9	999.9	999.9	999.9	999.9	999.9
		901 1 20 1 3	542.0	548.2	565.9	576.1	593.6	615.6	636.8	652.4	670.2	4.069	727.5	784.
		V COMP	•	-3.0	-3.1	-	0.4-	4.	- O. C.		9	D. 6-	-9.0	6.66
CALIF	1961	0 COMP	E. 2-	D	-6.7	8 .6		4.6	10.0	-13.6	-8	₹.	4.B-	99.9
STATION NO. TEMACHAPI, C	APRIL 1818 GNT	SPEED M/SEC	10°	M.	4.4	€. 9	M . Z		6.0	• •	19.6	12.7	9 .4	6.66
# T # T # T # T # T # T # T # T # T # T	*	018 06	112.3	23.1	65.3	99.9	36.9	65.5	6.09	56.1	50.5	.	20.7	4.665
		DEW PT	• •	99.9	99.9	99.9	6.66	6.66	6.66	6.66	6.66	99.9	9,0	96.0
		754P	-88.7	4.96-	-34.5	-54.1	-53.3	149.B	-40.9	-48.6	-48.2	D. 64-	-46.3	-41.7
		A TE TE	41.0	39.0	36.0	34.0	310	25.0	26.0	24.0	22.0	19.0	17.0	9. 11
		HE I GHT GP H	21941 0	22259.8	22770.3	23136.7	23730.4	24163.5	24879.8	25405.8	25978.6	26944.4	27680.1	20000
		CNTCT	135.0	156.0	157.0	158.0	159.0	160.0	161.0	162.0	163.0	164.0	165.0	166.0
		w #	•	'n	•	۲.	•	M	۲.	Ŋ	•	•	0	4

APPENDIX B

30-Second Data

PRECEDING PAGE BLANK NOT FILMED

STATION NO. 2 WHEELER RIDGE, CALIF

						14	APRIL 1535 G	19 0 1 HT
TIME	CHTCT	HEIGHT	PRES	TEMP DG C	DEU PT	DIR	SPEED	R HUH
HIN	6.7	GPM 168.0	MB 1001.4	17.0	DG C 8.7	350.0	H/SEC .5	PCT 58.0
0.0 .5	7.8	276.2	988.6	15.7	4.4	290.1	.3	47.0
1.0	9.3	410.0	972.3	14.4	3.6	239.2	. 6	47.9
1.5	11.0	578.6	954.0	14.1	3.4	243.3	2.0	48.7
2.0	12.5	716.9	938.5	13.7	3.7	244.4	1.8	50.8
2.5	14.3	982.1	920.3	13.0	3.0	219.5	. 4	50.8
3.0	15.5	1004.0	907.0	12.5	3.0	111.5	۰,6	52.5
3.5	16.8	1120.3	894 . 5	11.5	2.8	129.4	. 6	55.3
4.0	18.3	1270.9	878.5	10.6	2.5	55.7	. 4	57.0
4.5	19.5	1390.4	866.0	10.3	1.3	80.5	1.4	53.9
5.0	20.6	1503.0	654 .4	11.6	-1.8	123.7	3.4	39.4
5.5 6.0	22.0 23.5	1645.1 1785.6	840.0 826.0	11.9 11.2	-8.8 -9.3	135.7 118.2	6.1	22.4 22.7
6.5	24.6	1897.3	815.0	10.9	-0.5	115.5	7.5 8.9	24.6
7.0	25.8	2015.7	803.5	10.5	-8.1	118.9	9.5	26.0
7.5	27.0	2145.9	791.0	9 7	-0.2	122.9	9.5	27.4
8.0	28.5	2304.5	776.0	0.3	-8.5	124.3	9.6	29.3
8.5	29.8	2438.3	763.5	7.1	-0.5	125.9	9.6	32.1
9.0	31.0	2573.5	751.0	5.4	-9.3	127.5	10.0	33.6
9.5	32.3	2710.5	738.5	4.4	-9.5	126.8	11.1	35.6
10.0	33.5	2843.6	726.5	3.2	-10.1	126.8	11.4	37.0
10.5	34.8	2969.9	715.3	2.0	-11.5	127.8	11.4	35.9
11.0	36.3	3134.9	700.8	1.3	-13.5	130.9	10.6	32.3
11.5 12.0	37.5 38.6	3264.8 3387.5	689.5 679.0	2 -1.2	-14.2 -15.6	137.4	9.4	33.0 32 4
12.5	39.8	3514.6	668.3	-1.3	-18.3	146.4 155.7	8.7 8.5	26.1
13.0	41.3	3680.3	654.5	-1.6	-23.0	167.2	7.3	17.6
13.5	42.5	3821.1	643.0	-2.5	-24.3	183.7	5.7	16.8
14.0	43.6	3937.8	633.6	-3.2	-25.2	190.3	4.9	16.4
14.5	44.8	4067.8	623.3	-4.5	-26.1	161.4	4.4	16.4
15.0	46.0	4210.8	612.0	-5.5	-27.0	166.2	4.2	16.4
15.5	47.3	4356.1	600.0	-6.5	-27.8	163.8	4.1	16.4
16.0	48.4	4491.9	590.4	-6.9	-28.2	170.7	4.0	16.3
16.5	49.5	4623.7	580.5	-7.5	-28.6	182.0	3.9	16.6
17.0	50.6	4749.2	571.2	-7.9	-28.8	193.3	3.6	16.7
17. 5 18.0	51.8 53.0	4885.6	561.3	-8.8	-28 6	202.3	3.1	18.3
18.5	54.3	5027.9 5183.3	551.0 540.0	-10.0 -10.9	-29.2 -30.0	202.9	2.6	18.9
19.0	55.5	5333.9	529.5	-12.2	-30.0 -30.9	1 96.8 203.0	2.5 2.3	19.0 19.3
19.5	56.6	5469.0	520.2	-13.5	-31.9	214.8	2.2	19.3
20.0	57.6	5586.6	512.2	-14.6	-32.8	214.1	2.2	19.4
20.5	58.8	5723.6	503.0	-16.0	-34.0	200.8	2.4	19.4
21.0	60.0	5874.4	493.0	-17.0	-34.8	190.2	2.6	19.4
21.5	61.3	6024.1	483.0	-18.0	-35.8	193.6	2.2	19.2
22.0	62.4	6177.9	473.4	-19.3	-36.5	204.6	1.7	20.0
22.5	63.4	6307.4	465.2	-20.5	-36.9	212.4	1.4	21.3
23.0	64.5	6438.8	457.0	-21.8	-36.9	207.8	1.5	23.7
23.5	65 · 8	6588.9	447.8	-23.4	-37.2	206.5	1.8	26.7
24.0 24.5	67.0 68.3	6749.4 6912.7	438.0 420.3	-24.9	-35.8	213.4	2.0	35.1
47.3	50.3	9716.7	740.3	-26.6	-37.4	231.4	1.7	34.9

STATION NO. 2 UHEELER RIDGE, CALIF

1981

14 APRIL

							1535 GI	1T
TIME	CHTCT	HEIGHT	PRES	TEMP	DEU PT	DIR	SPEED	R HUH
HIH		GPN	ND	DG C	DG C	DG	M/SEC	PCT
25.0	69.4	7049.4	420.2	-26.2	-38.6	251.9	1.6	35.6
25.5	70.5	7190.5	412.0	-29.6	-39.8	263.4	1.8	36.3
26.0	71.6	7333.5	403.8	-30.6	-40.6	267.4	2.1	36.4
26.5	72.6	7468.4	396.2	-31.4	-41.4	266.8	2.4	36.4
27.0	73.6	7590.6	389.4	-32.3	-42.2	256.6	2.5	36.6
27.5	74.9	7730.3	381.8	-33.5	-43.1	238.7	2.6	36.7
28.0	75.8	7891.7	373.6	-33.9	-43.7	227.2	2.7	36.3
28.5	77.0	6044.3	365.0	-35.3	-44.9	227.8	2.6	36.3
29.0	78.3	8193.3	35 7.3	-37.3	-46.6	240.8	2.7	36 . 5
29.5	79.4	8350.4	349.2	-38.8	-48.1	255.2	3.2	36.1
30.0	80.4	8489.0	342.2	-40.1	99.9	265.1	3.5	999.9
30.5	81.4	8621.6	335.6	-41.1	99.9	278.2	3.4	999.9
31.0	82.4	8743.9	329.6	-42.4	99.9	273.9	3.6	999.9
31.5	83.7	8915.3	321.3	-43.4	99 .9	281.1	2.6	999.9
32.0	84.7	9048.6	315.0	-44.5	99 .9	264.8	2.4	999.9
32.5	85.8	9188.0	308.5	-46.0	99.9	279.7	2.3	999.9
33.0	86.8	9342.7	301.4	-46.9	99 .9	277.4	2.8	999.9
33.5	87.8	9480.2	295.2	-47.4	99 .9	2 8 0.9	3.6	999.9
34.0	88.8	9615.8	289.2	-48.2	99 .9	203.6	4.3	999.9
34.5	89.8	9753.4	283 .2	-49.9	99 .9	288.5	5.2	999.9
35.0	90.8	9893.2	277.2	-50.9	99.9	294.1	6.5	999.9
35.5	91.8	10035.4	271.2	-51.9	99.9	294.6	7.6	999.9
36.0	93.0	10184.6	265.0	-53.2	99.9	288.7	8.2	999.9
36.5	94.0	10332.0	259 .0	-53.8	99.9	280.1	9.0	999.9
37.0	95.0	10482.0	25 3.0	-55.4	99 .9	277.6	9.5	999.9
37.5	96.2	10640.3	246.8	-55.9	99.9	281.0	9.8	999.9
38.0	97.3	10797.9	240.8	-56.9	99.9	285.1	10.6	999.9
38.5	98.4	10950.7	235.0	-58.0	99.9	288.8	11.7	999.9
39.0	99.4	11097.1	229.6	-58.8	99.9	291.5	12.1	999.9
39.5	100.4	11251.7	224.0	-59.5	99.9	292.6	11.8	999.9
40.0	101.4	11393.0	219.0	-59.6	99.9	290.9	11.0	999.9
40.5	102.4	11537.4	214.0	-59.8	99.9	285.8	10.5	999.9
41.0	103.5	11700.2	208.5	-59.8	99.9	280.2	10.5	999.9
41.5	104.6	11867.0	203.0	-60.4	99.9	277.3	10.8	999.9
42.0	105.6	12022.2	198.0	-61.1	99.9	274.7	10.9	999.9
42.5	106.6	12181.1	193.0	-61.0	99.9	269.9	1:.0	999.9
43.0	107.6	12344.5	188.0	-69.5	99.9	263.1	11.1	999.9
43.5	108.6	12492.0	183.6	-59.7	99.9	257.1	11.5	999.9
44.6	109.6	12651.4	179.0	-58.6	99.9	253.7	12.0	999.9
44.5	110.6	12807.8	174.6	-58.2	99.9	252.0	12.7	999.9
45,0	111.6	12976.1	170.0	-58.1	99.9	250.7	13.4	999.9
45.5	112.5	13125.9	166.0	-56.2	99.9	249.4	13.7	999.9
46.0	113,4	13264.0	162.4	-58.2	99.9	248.1	13.6	999.9
46.5	114.4	13437.3	158.0	-57.9	99.9	246.3	13.2	999.9
47.0	115.4	13623.5	153.4	-57.7	99.9	244.4	12.8	999.9
47.5	116.3	13778.8	149.7	-58.2	99.9	243.0	12.8	999.9
48.0	117.2	13920.3	146.3	-58.5	99.9	242.7	13.5	999.9
48.5	118.0	14064.7	143.0	-59.1	99.9	243:6	14.9	999.9
49.0	118.8	14212.9	139.7	-59.1 -59.5	99.9	245.5	15.0	999.9 999.9
49.5	119.7	14364.5	136.3	-37.3	99.9	245.7	15.7	フフラ・ブ

STATION NO. 2 WHEELER RIDGE, CALIF

						14	APRIL	1981
							1535 G	MT
TIME	CHTCT	HEIGHT	PRES	TEMP	DEW PT	DIR	SPEED	R HUH
HIN	CHICI	GPM	MB	DG C	DG C	DG	H/SEC	PCT
50.0	120.5	14519.6	133.0	-59.5	99.9	243.7	15.3	999.9
50.5	121.4	14671.7	129.0	-59.3	99.9	248.4	15.4	999.9
51.0	122.3	14825.3	126.7	-59.0	99.9	238.6	16.7	999.9
51.5	123.2	14992.5	123.3	-58.4	99.9	240.2	17.9	999.9
52.0	124.0	15164.4	120.0	-58.4	99.9	244.7	17.5	999.9
52.5	124.8	15297.2	117.5	-58 . 1	99.9	249.4	16.2	999.9
53.0	125.7	15469.8	114.3	-58.1	99.9	250.1	15.2	999.9
53. 5	126.5	15627.7	111.5	-58 . 1	99.9	247.4	14.2	999.9
54.0	127.3	15770.5	109.0	-58.0	99.9	243.5	13.3	999.9
54 . 5	128.2	15926.8	106.3	-57.9	99.9	240.2	12.4	999.9
55.0	129.0	16127.1	103.0	-57.6	99.9	235.9	10.7	999.9
55.5	129.8	16282.0	100.5	-59.0	99.9	225.1	9.8	999.9
56.0	130.7	16440.1	98.0	-59.6	99.9	217.5	10.4	999.9
56.5	131.5	16601.5	95.5	-60.3	99.9	214.9	11.3	999.9
57.0	132.3	16757.1	93.1	-60.9	99.9	214.9	12.0 12.5	999. 9 999.9
57 · 5	133.0	16901.1	91.0	-60.9 -60.9	99.9 99.9	215.2 216.4	13.8	999.9
58.0 58.5	133.7 134.5	17850.0 17217.4	88.9 86.5	-60.9	99.9	219.2	14.7	999.9
59.0	135.3	17381.2	84.3	-60.7	99.9	222.9	14.8	999.9
59.5	135.9	17521.0	82.4	-60.4	99.9	226.7	14.1	999.9
60.0	136.7	17704.3	80.0	-59.5	99.9	229.3	13.5	999.9
60.5	137.4	17886 . 4	77.7	-58.5	99.9	233.1	13.4	999.9
61.0	138.1	18057.2	75.6	-57.8	99.9	237.6	13.4	999.9
61.5	138.8	18215.9	73.8	-58.0	99.9	242.1	12.6	999.9
62.0	139.4	18354.5	72.1	-57.9	99.9	246.0	11.3	999.9
62.5	140.1	18498.8	70.6	-57.5	99.9	248.2	9.8	999.9
63.0	140.8	18659.4	68.8	-57.1	99.5	241.9	8.5	999.9
63.5	141.4	18850.5	66.7	-56.5	9 9.9	231.4	6.7	999.9
64.0	142.1	19042.6	64.7	-55.9	99.9	214.2	5.0	999.9
64.5	142.9	19184.6	63.3	-55.9	99 .9	202.5	4.4	999.9
65.0	143.5	19368.0	61.5	-56.3	99.9	199.6	4.7	999,9
65.5	144.1	19546 . 8	59.8	-56.7	99.5	201.5	5.2	999.9
66.0	144.7	19666.3	58.7	-56.6	99.9	211.7	5.6	999.9
66.5	145.3	19822.2	57.3	-56.5	99.9	219.0	6.0	999.9
67 0	145.9	20032.8	55.4	-56.4 -56.5	99.9 99.9	223.6 226.6	6.2 6.5	999.9 999.9
67.5	146.5 147.1	20192.5 20356.2	54.0 52.6	-56.7	99.9	230 3	6.6	999.9
68.0 68.5	147.8	20586.8	50.7	-57.2	99.9	240.1	5.8	999.9
69.0	148.3	20756.5	49.4	-57.2	99.9	247.3	4.5	999.9
69.5	148.8	20885.7	48.4	-56.9	99.9	255.4	3.0	999.9
70.0	149.3	21073.8	47.0	-56.7	99.9	248.8	. 8	999.9
70.5	149.9	21301.1	45.3	-56.7	99.9	95.8	1.9	999.9
71.0	150.4	21474.7	44.1	-56.6	99.9	108.3	2.7	999.9
71.5	151.0	21635.0	43.0	-56.4	99.9	122.3	3.1	999.9
72.0	151.5	21864.7	41.5	-56.2	99.9	138.4	1.0	999.9
72.5	152.0	22094.5	40.0	-56.1	99.9	279.8	1.3	999.9
73.0	152.5	22242.8	39.1	-55.9	99.9	3.6	3.1	999.9
73.5	152.9	22391.2	38.2	-55.8	99 .9	16.0	6.2	999.9
74.0	153.4	22559.2	37.2	-55.0	99.9	25.9	6.2	999.9
74.5	153.9	22732.1	36.2	-54.0	99.9	39.4	5.6	999.9

STATION NO. 2 WHEELER RIDGE, CALIF

						14	MAKIF	1981
							1535 G	HT
T. 45	AU 7.07		PRES	TEMP	DEW PT	DIR	SPEED	R HUM
TIME	CHTCT	HEIGHT	rkes MB	DG C	DG C	DG	M/SEC	PCT
HIN	454.4	GPH	34.8	-53.6	99.9	46.7	5.6	999.9
75.0	154.4	22990.7				52.1	5.7	999.9
75.5	154.9	23270.6	33.3	-53.3	99.9	51.6	6.8	999.9
76.0	155.3	23450.1	32.4	-53.6	99.9	50.3	8.1	999.9
76.5	155.7	23604.5	31.6	-54.2	99.9			999.9
77.0	156 . 1	23774.7	30 8	-54.5	99.9	49.9	9.3	
77.5	156.4	24008.1	29.7	-54.1	99.9	51.8	9.8	999.9
78.0	156.8	24241.5	28.6	-53.6	99.9	53.5	10.4	999.9
78.5	157 - 1	24445.5	27.7	-53.0	99.9	53.1	10.9	999.9
79.0	157.5	24605.6	27.1	-52.1	99.9	50.0	11.5	999.9
79.5	157.8	24765.6	26.4	-51.1	99.9	47.2	12.0	999.9
80.0	158.2	24941 9	25.7	-50.6	99.9	42.3	12.4	999.9
80.5	158.5	25142.5	24.9	-50.7	99.9	34.0	12.6	999.9
81.0	158.9	25343.1	24.2	-50.9	99.9	26.0	13.0	999.9
91.5	159.2	25589.0	23.3	-50.2	99.9	27.2	12.2	999.9
82.0	159.5	25846.2	22.4	-49.5	99.9	31.3	11.1	999.9
82.5	159.8	26103.5	21.5	-48.7	99.9	36.3	10.0	999.9
83.0	160.1	26359.5	20.7	-48.1	99 .9	37.6	9.6	999.9
83.5	160.4	26613.7	20.0	-48.0	99 . 9	32.4	9.9	999.9
84.0	160.6	26867.9	19.2	-47.9	99.9	27.6	10.4	999.9
84.5	160.9	27122.1	18.5	-47.8	99.9	23.2	10.9	999.9
9 5 .0	161.1	27337.6	17.8	-47.3	99.9	20.8	11.1	999.9
85.5	161.3	27495.2	17.4	-46.1	99.9	21.0	10.8	999.9
96.0	161.5	27652.8	17.0	-44.9	99.9	21.2	10.4	999.9
86.5	161.7	27810.4	16.6	-43.7	99.9	21.5	10.1	999.9
87.0	161.9	27968.0	16.2	-42.5	99.9	21.7	9.8	999.9
87.5	162.1	28179.9	15.8	-41.6	99.9	999.9	99.9	999.9
88.0	162.3	28473.4	15.1	-41.6	99.9	999.9	99. 9	999.9
88.5	162.5	28766.9	14.5	-41.5	99.9	999.9	99.9	999.9
89.0	162.7	29060.4	13.9	-41.4	99.9	999.9	99.9	999.9
89.5	162.9	29353.9	13.2	-41.3	99.9	999.9	99.9	999.9

TIME CHTCT MEIGHT GPM M8 DG C DG C DG M/9EC PCT 0.0 19.1 1366.0 667.4 9.0 3.8 66.0 4.1 70.0 3.9 1.0 1.0 22.0 1685.3 835.0 12.7 -8.8 96.4 6.3 21.4 1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 8.0 21.4 1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 8.0 21.4 1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 8.0 21.4 1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 8.0 21.4 1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 8.0 21.4 1.5 2.5 26.3 2132.2 791.5 9.5 -8.8 117.5 -8.4 109.6 8.5 23.9 2.5 26.3 2132.2 791.5 9.5 -8.8 117.5 -8.4 109.6 8.5 23.9 2.5 26.3 2132.2 7791.5 9.5 -8.8 117.5 1.0 10.8 36.9 29.8 3.5 299.0 2424.5 764.0 7.3 -7.8 116.0 10.3 33.1 4.0 30.5 2587.4 749.0 5.7 -7.9 113.0 10.8 36.9 4.5 31.8 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 1.5 33.3 3291.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.5 34.5 3227. 709.5 1.4 -8.6 115.2 11.6 47.3 45.5 46.0 37.3 3326.2 683.5 -1.7 -1.2 2.9 13.4 10.0 10.8 36.9 6.5 37.3 3326.2 683.5 -1.7 -1.2 2.9 13.4 10.0 10.0 16.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 40.9 13.9 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 19.5 39.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 19.5 39.0 44.8 4185.1 623.0 -7.0 -27.8 156.0 9.5 17.1 10.5 16.4 19.5 30.9 602.0 -7.0 -27.8 156.0 9.5 17.1 10.5 16.4 19.5 30.9 602.0 -7.0 -27.8 156.0 9.5 17.1 10.5 16.4 19.5 30.9 602.0 -7.0 -27.8 156.0 9.5 17.1 10.5 16.4 19.5 30.9 602.0 -7.0 -27.8 156.0 9.5 17.1 10.5 16.4 19.5 30.5 30.5 154.5 570.6 6.9 5.5 1.1 -7 -32.1 187.5 2.3 16.4 11.5 57.9 10.5 16.8 30.1 10.0 57.5 570.2 -9.5 50.4 41.0 57.5 570.2 -9.5 50.4 47.3 4476.7 590.8 -8.1 -29.9 174.3 5.4 16.1 17.5 50.9 50.0 44.8 4185.1 623.3 -1.7 -32.1 187.5 2.3 16.4 11.5 50.9 50.0 50.0 50.0 50.0 50.0 50.0 50							14	APRIL 1541 GI	1981
NIN								1341 61	"
0.0 19.1 1366.0 867.4 9.0 3.6 60.0 4.1 70.0 1.3 20.5 1531.0 850.5 13.4 -2.7 93.0 4.9 34.9 1.0 22.0 1685.3 835.0 12.7 -8.8 86.4 6.3 21.4 1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 6.0 21.7 2.0 24.8 1976.0 806.5 11.5 -8.4 109.6 8.5 23.9 22.5 26.3 2132.2 791.5 9.5 -8.8 117.5 6.3 22.6 5 3.0 27.5 22.64.2 791.5 9.5 -8.8 117.5 6.3 22.6 5 3.0 27.5 22.64.2 779.0 8.9 -7.8 116.0 10.3 33.1 4.0 30.5 2587.4 749.0 5.7 -7.9 113.0 10.8 33.1 4.0 30.5 2587.4 749.0 5.7 -7.9 113.0 10.8 33.1 4.0 30.5 2587.4 749.0 5.7 -7.9 113.0 10.8 33.1 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 6.9 37.3 3326.2 693.5 -1.7 -12.7 12.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 16.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 11.5 50.8 6.5 37.3 326.9 660.3 -2.0 -24.3 144.3 9.3 16.2 11.5 50.8 6.5 42.3 3869.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.1 6.1 6.5 42.3 3869.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.5 44.8 4475.1 570.2 -9.5 -30.4 186.0 3.5 16.1 6.2 10.5 16.4 49.5 44.8 4485.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.5 44.8 4485.1 570.2 -9.5 -30.4 186.0 3.5 16.1 10.5 16.4 49.5 44.8 4485.1 613.3 -5.7 -26.9 153.9 10.2 16.8 11.5 50.6 468.0 -7.0 -7.0 -7.0 -7.0 16.8 6.2 17.7 16.1 15.7 16.1 15.7 16.5 16.4 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 11.5 50.6 4751.0 570.2 -7.0 -7.0 -7.0 -7.0 17.0 17.5 17.5 17.5 17.5 17.5 17.5 17.5 17.5	TIME	CHTCT	HEIGHT	PRES	TEMP	DEW PT	DIR	SPEED	R HUM
1.0 22.0 1695.3 e35.0 12.7 -e8.9 86.4 6.3 21.4 1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 8.0 21.7 2.0 24.8 1976.0 806.5 11.5 -8.4 109.6 8.5 23.9 25.5 26.3 2132.2 791.5 9.5 -8.8 117.5 8.3 26.5 3.0 27.5 2264.2 779.0 8.9 -7.8 116.0 8.9 29.8 3.5 29.0 2424.5 764.0 7.3 -7.8 116.0 10.5 33.1 4.0 30.5 2587.4 749.0 5.7 -7.9 113.0 10.8 36.9 4.5 31.8 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 5.0 30.5 2587.4 749.0 5.7 -7.9 113.0 10.8 36.9 4.5 31.8 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 5.0 33.3 32891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.5 34.5 3027.7 799.5 1.4 -8.6 115.2 11.6 47.3 5.5 34.5 3027.7 799.5 1.4 -8.6 115.2 11.6 47.3 5.6 37.3 326.2 683.5 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 3.9 3 16.2 8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 10.5 42.3 3889.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 44.8 4185.1 663.3 -5.7 -26.9 153.9 10.5 16.4 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.0 9.5 17.1 10.1 5.7 9.0 43.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.0 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 15.7 16.4 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.1 17.6 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 13.0 53.0 5154.5 530.4 -13.1 -32.7 210.2 22.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 50.6 5962.2 486.2 -18.0 -36.9 187.4 221.6 2.1 17.6 18.6 19.0 596.6 460.0 49.2 -18.8 36.5 172.1 2.2 19.3 16.9 17.5 16.6 49.0 -20.2 -34.4 16.4 1.8 26.9 17.5 50.6 64.0 6506.1 476.2 -18.8 36.5 172.1 2.2 19.3 16.5 16.5 50.6 64.0 6506.1 476.2 -18.8 36.5 172.1 2.2 19.3 16.9 17.5 50.6 64.0 6506.1 476.2 -18.8 36.5 172.1 2.2 19.3 16.5 17.5 50.0 66.4 6812.8 433.2 -25.5 36.9 35.0 35.1 1.2 33.1 2.3 32.7 2.2 1.5 5.3 6666.5 442.0 -24.0 -35.6 93.5 11.2 33.1 2.3 32.7 2.2 1	HIH		CPM	MB	DG C	DG C	DG	M/SEC	PCT
1.0 22.0 1685.3 635.0 12.7 -8.8 86.4 6.3 21.7 1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 8.0 21.7 2.0 24.8 1976.0 806.5 11.5 -8.4 109.6 8.5 23.9 2.5 26.3 2132.2 791.5 9.5 -8.8 117.5 8.3 26.5 3.0 227.5 2244.2 779.0 8.9 -7.8 116.0 8.9 29.8 3.5 29.0 2424.5 764.0 7.3 -7.8 116.0 10.5 33.1 4.0 30.5 2587.4 749.0 5.7 -7.9 113.0 10.8 36.9 4.5 31.8 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.5 34.5 3027.7 709.5 1.4 -8.6 115.2 11.6 47.3 6.0 35.8 3164.2 697.5 .2 -8.8 116.2 11.5 50.8 6.5 37.3 3326.2 683.5 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 6.5 40.3 375.1 648.0 -2.2 -24.3 144.3 9.3 16.2 6.5 40.5 40.5 40.5 40.5 40.5 40.5 40.5 40	0.0	19.1	1366.0	867.4	9.0	3.8	60.0	4.1	70.0
1.5 23.5 1842.4 819.5 12.1 -9.1 95.5 8.0 21.7 2.0 24.8 1976.0 806.5 11.5 -8.4 109.6 8.5 23.9 2.5 26.3 2132.2 791.5 9.5 -8.8 117.5 8.3 26.5 3.0 27.5 2264.2 779.0 8.9 -7.8 116.8 8.9 29.8 3.5 29.0 2424.5 764.0 7.3 -7.8 116.0 8.9 29.8 4.5 33.1 27.5 2587.4 749.0 5.7 -7.9 110.1 11.2 40.4 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.3 31.8 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 5.0 33.3 32891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.5 34.5 3027.7 799.5 1.4 -8.6 115.2 11.6 47.3 5.5 34.5 3027.7 799.5 1.4 -8.6 115.2 11.6 47.3 5.5 34.5 3027.7 799.5 1.4 -8.6 115.2 11.6 47.3 5.6 37.3 326.2 689.5 -1.7 -12.7 122.4 11.0 16.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.0 41.0 3759.1 640.0 -2.2 -24.3 144.3 9.3 16.2 8.0 41.0 3759.1 640.0 -2.2 -24.3 144.3 9.3 16.2 8.0 41.0 3759.1 640.0 -2.2 -24.3 152.7 9.5 16.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 18.5 19.6 48.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 44.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.8 2.1 17.6 14.5 57.6 5576.6 570.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.8 2.1 17.5 15.5 56.4 5576.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 11.7 17.5 18.0 64.0 6502.6 452.0 -21.8 -35.2 221.0 2.5 17.5 17.5 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 2.2 19.3 16.9 17.5 18.0 500.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 2.2 17.7 17.5 63.0 666.5 442.0 -24.0 -35.6 59.5 77.3 1.0 33.7 2.2 17.5 17.5 63.0 666.5 442.0 -24.0 -35.6 59.5 77.3 1.0 33.7 2.2 17.5 17.5 63.0 666.5 442.0 -24.0 -35.6 59.5 77.3 3.2 19.0 66.4 6812.8 433.2 -25.5 36.0 35.9 35.1 1.3 33.5 2.2 17.5 77.6 -33.8 -44.3 229.5 9.3 33.7 2.2 17.5 77.0 77.0 77.0 77.0 77		20.5	1531.0	850.5	13.4	-2.7	93.0	4.9	34.9
2.0	1.0	22.0	1605.3	835.0	12.7	-8.8	86.4	6.3	21.4
2.5	1.5	23.5	1842.4	819.5	12.1		95.5	8.0	21.7
3.0 27.5 2264 2 779.0 8.9 -7.8 116.8 8.9 29.8 3.5 29.0 2424.5 764.0 7.3 -7.8 116.0 10.3 33.1 4.0 30.5 2587.4 749.0 5.7 -7.9 116.0 10.8 36.9 4.5 31.9 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.5 34.5 3027.7 799.5 1.4 -8.6 115.2 11.6 47.3 6.0 35.8 3164.2 697.5 .2 -8.8 116.2 11.5 50.8 6.5 37.3 3326.2 643.5 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3889.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 379.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 23.1 16.4 13.5 54.2 5305.6 550.4 -13.1 -32.7 210.2 2.1 17.4 14.5 56.4 5576.6 551.8 -15.2 -34.2 223.8 2.4 17.7 15.0 55.3 543.0 494.2 -17.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 550.4 -13.1 -32.7 210.2 2.1 17.6 14.5 56.4 659.6 5962.2 466.2 -18.8 -36.5 172.1 2.2 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 466.2 -18.0 -36.9 187.4 221.6 2.1 17.6 14.5 56.4 6937.6 459.0 -20.2 -34.4 162.4 1.8 26.9 17.5 66.4 6937.6 459.0 -20.2 -34.4 162.4 1.8 26.9 17.5 66.4 6937.6 459.0 -20.2 -34.4 162.4 1.8 26.9 17.5 66.4 6937.6 459.0 -20.2 -34.4 162.4 1.8 26.9 17.5 67.4 6937.6 455.8 -26.7 -38.1 331.1 2.0 32.7 19.0 66.4 6937.6 455.8 -26.7 -38.1 331.1 2.0 32.7 19.0 66.4 6937.6 455.8 -26.7 -38.1 331.1 2.0 32.7 19.0 66.4 6937.6 455.8 -26.7 -38.1 331.1 2.0 32.7 19.5 66.4 6937.6 455.8 -26.7 -38.1 331.1 2.0 32.7 19.5 66.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 19.5 66.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 19.5 66.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 19.5 66.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 19.5	2.0	24.8	1976.0	806.5	11.5	-8.4	109.6	8.5	23.9
3.5 29.0 2424.5 764.0 7.3 -7.8 116.0 10.5 33.1 4.0 30.5 2587.4 7749.0 5.7 -7.9 113.0 10.8 36.9 4.5 31.8 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.5 34.5 3027., 709.5 1.4 -8.6 115.2 11.6 47.3 6.0 35.8 3164.2 697.5 .2 -8.8 116.2 11.5 50.8 6.3 37.3 3326.2 683.3 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.5 42.3 3899	2.5	26.3	2132.2	791.5	9.5	-8.8	117.5	0.3	26.5
4.0 30.5 2587.4 749.0 5.7 -7.9 113.0 10.8 36.9 4.5 31.8 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.5 34.5 3027.7 709.5 1.4 -8.6 115.2 11.6 47.3 6.0 35.8 3164.2 697.5 .2 -8.8 116.2 11.5 50.8 6.3 37.3 3326.2 683.3 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3889.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 \$79.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 \$70.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 \$51.3 -11.7 -32.1 189.9 2.5 16.3 12.5 51.8 5011.0 \$551.3 -11.7 -32.1 189.9 2.5 16.3 12.5 51.8 5011.0 \$551.3 -11.7 -32.1 187.5 2.3 16.4 13.5 \$4.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 \$21.8 -14.1 -33.4 221.8 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 2.3 16.8 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 66.4 6812.9 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.0 -22.8 -35.1 129.4 2.2 17.5 19.5 67.4 6937.6 425.0 -22.8 -35.1 129.4 2.2 17.1 16.5 60.6 60.6 60.6 1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 666.5 442.0 -22.8 -35.1 129.4 2.2 17.1 16.5 60.6 60.6 60.6 452.0 -22.8 -35.1 129.4 2.2 17.1 16.5 60.6 60.6 60.6 452.0 -22.8 -35.1 129.4 2.2 17.1 16.5 60.6 60.6 60.6 452.0 -22.8 -35.1 129.4 2.2 17.1 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 666.5 442.0 -35.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.5 19.0 66.4 6912.9 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 33.5 22.5 74.2 7	3.0	27.5	2264.2	779.0		-7.8	116.8	8.9	29.8
4.5 31.8 2724.7 736.5 4.4 -7.9 110.1 11.2 40.4 5.5 33.3 2891.7 721.3 2.6 -8.2 111.2 111.7 44.5 5.5 34.5 3027., 709.5 1.4 -8.6 115.2 111.6 47.3 60.0 35.8 3164.2 697.5 .2 -8.8 116.2 111.5 50.8 6.5 37.3 3326.2 683.5 -1.7 -12.7 122.4 111.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 80.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3889.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 44.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.3 11.0 48.5 4625.9 579.5 -8.6 -29.9 174.3 5.4 16.1 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -11.7 -32.1 187.5 2.3 16.4 13.5 55.3 5430.7 521.8 -14.1 33.4 221.6 2.1 17.6 14.5 55.3 5430.7 521.8 -14.1 33.4 221.6 2.1 17.6 14.5 55.3 5430.7 521.8 -14.1 33.4 221.6 2.1 17.6 14.5 55.3 5430.7 521.8 -14.1 33.4 221.6 2.1 17.6 14.5 55.3 5430.7 521.8 -14.1 33.4 221.6 2.1 17.6 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 668.6 459.0 -21.8 -36.9 172.1 2.2 17.1 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 2.2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 98.5 11. 29.4 2.2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 98.5 11. 29.4 2.3 16.8 16.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 2.2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 98.5 11. 29.4 2.2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 98.5 11. 29.4 2.2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 98.5 11. 29.4 2.2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 98.5 11. 29.4 2.2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 98.5 11. 29.4 2.2 31.3 32.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 410.5 -28.9 -40.1 294.7 2.4 32.9 21.5 71.0 70.6 7335.9 402.8 -30.9 -41.7 266.9 355.1 1.3 33.5 22.5 74.2 7792.7 3776.6 -35.0 -45.3 222.3 9.9 34.0		29.0							
5.0 33.3 2891.7 721.5 2.6 -8.2 111.2 11.7 44.5 5.5 34.5 3027.7 709.5 1.4 -8.6 115.2 11.6 47.3 6.0 35.8 3164.2 697.5 .2 -8.8 116.2 11.5 50.8 6.5 37.3 3326.2 683.5 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3689.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8									
5.5 34.5 3027. 709.5 1.4 -8.6 115.2 11.6 47.3 6.0 35.8 3164.2 697.5 .2 -8.8 116.2 11.5 50.8 6.5 37.3 3326.2 683.5 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3689.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 155.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.9 163.7 7.8 16.3						_			
6.0 35.8 3164.2 697.5 .2 -0.8 116.2 11.5 50.8 6.5 37.3 3326.2 603.5 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3809.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4105.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 44.0 4329.8 602.0 -7.0 -27.0 156.0 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 379.5 -0.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 370.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4860.2 561.6 -10.5 -31.1 109.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 59.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 21.7 1.3 1.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 21.3 1.3 19.5 65.5 65.5 720.7 410.5 -22.9 -40.1 294.7 2.4 32.9 19.0 66.4 6812.9 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 65.5 720.7 410.5 -28.9 -40.1 294.7 2.4 32.9 22.5 72.0 73.0 7637.9 377.6 -33.0 -40.9 282.7 2.1 33.4 22.5 73.5 19.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 22.5 71.0 70.6 7335.9 402.0 -30.0 -40.9 282.7 2.1 33.4 22.5 71.5 71.8 7479.4 394.0 -30.9 -41.7 266.9 1.5 33.4 22.5 77.5 7923.5 370.6 -35.0 -45.3 22.2 3.9 34.0									
6.5 37.3 3326.2 683.5 -1.7 -12.7 122.4 11.0 45.9 7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3889.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 351.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.6 5962.2 486.2 -18.0 -36.9 187.4 221.6 2.1 17.6 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 630.6 459.0 -21.6 -35.1 129.4 2.2 17.1 18.0 66.4 6812.8 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 630.6 6452.0 -22.8 -35.1 129.4 2.2 17.1 18.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 129.4 2.2 17.1 18.0 66.4 6912.8 433.2 -25.5 -36.9 359.1 1.3 32.7 21.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.0 32.7 22.5 71.8 7479.4 394.8 -30.9 -44.1 294.7 2.4 32.9 21.5 71.8 7479.4 394.8 -30.9 -40.1 294.7 2.4 32.9 22.5 71.5 71.8 7479.4 394.8 -30.9 -40.1 294.7 2.4 32.9 33.7 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 9 33.7 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 9 33.7 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 9 33.7 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 9 33.7 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 9 33.7 22.5 74.2 7792.3 370.6 -35.0 -45.3 222.3 9 34.0									
7.0 38.4 3456.6 672.4 -1.7 -22.9 134.4 10.0 18.0 7.5 39.7 3600.5 660.3 -2.0 -24.3 144.3 9.3 16.2 8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3889.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.9 163.7 7.8 16.3 11.0 48.5 4625.9 379.5 -8.8 -29.9 174.3 3.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>									
7.5									
8.0 41.0 3750.1 648.0 -2.2 -24.5 152.7 9.5 16.1 8.5 42.3 3689.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 551.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 551.3 -11.7 -32.1 187.5 2.3 16.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 586.5 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 606.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 17.4 7.7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 2.2 31.3 18.5 65.3 6666.5 442.0 -22.8 -35.1 129.4 2.2 31.3 18.5 65.3 6666.5 442.0 -22.8 -35.1 129.4 2.2 31.3 18.5 65.3 6666.5 442.0 -22.8 -35.1 129.4 2.2 31.3 18.5 67.4 6937.6 459.0 -21.6 -34.1 17.4 7.7 31.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 720.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 396.0 -32.5 -43.1 253.1 .9 33.5 72.2 22.0 73.0 7637.8 396.0 -32.5 -43.1 253.1 .9 33.7 22.5 74.2 7792.7 377.6 -33.8 -44.3 222.3 .9 34.0									
8.5 42.3 3889.0 636.8 -3.4 -25.7 154.7 10.1 15.7 9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.2 210.2 2.1 17.4									
9.0 43.5 4036.1 625.0 -4.3 -26.1 154.0 10.5 16.4 9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 16.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -333.4 221.8 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 22.0 73.0 7467.4 394.8 -30.9 -44.7 266.9 1.5 33.4 22.0 73.0 7467.4 394.8 -30.9 -44.7 266.9 1.5 33.4 22.0 73.0 7467.4 394.8 -30.9 -44.3 229.5 .9 33.7 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0	_	_	_				-		
9.5 44.8 4185.1 613.3 -5.7 -26.9 153.9 10.2 16.8 10.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.0 -36.9 187.4 2.2 17.1 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 219.3 19.0 66.4 6812.8 433.2 -25.5 36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6912.8 433.2 -25.5 36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 386.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 22.5 .9 33.7 23.0 75.2 7923.5 370.6 -33.0 -45.3 22.3 .9 34.0									
10.0 46.0 4329.8 602.0 -7.0 -27.8 156.8 9.5 17.1 10.5 47.3 4476.7 590.8 -8.1 -29.2 163.7 7.8 16.3 11.0 48.5 4625.9 579.5 -8.6 -29.9 174.3 5.4 16.3 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>									
10.5									
11.0 48.5 4625.9 579.5 -8.8 -29.9 174.3 5.4 16.1 11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5440.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 419.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 386.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0									
11.5 49.6 4751.0 570.2 -9.5 -30.4 186.0 3.5 16.4 12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.4 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.5 172.1 2.2 17.1 <									
12.0 50.6 4868.2 561.6 -10.5 -31.1 189.9 2.5 16.3 12.5 51.8 5011.0 551.3 -11.7 -32.1 187.5 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9									
12.5 51.8 5011.0 551.3 -11.7 -32.1 197.5 2.3 16.4 13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.8 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9									
13.0 53.0 5154.5 541.0 -12.2 -32.6 192.1 2.3 16.4 13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.6 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 <									
13.5 54.2 5305.6 530.4 -13.1 -32.7 210.2 2.1 17.4 14.0 55.3 5430.7 521.8 -14.1 -33.4 221.8 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 17.1									
14.0 55.3 5430.7 521.8 -14.1 -33.4 221.8 2.1 17.6 14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>									
14.5 56.4 5576.6 511.8 -15.2 -34.2 223.8 2.4 17.7 15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 <td></td> <td></td> <td></td> <td></td> <td></td> <td>-32.7</td> <td></td> <td></td> <td></td>						-32.7			
15.0 57.5 5707.4 503.0 -16.2 -35.2 221.0 2.5 17.5 15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 <td></td> <td>-</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>		-							
15.5 58.6 5840.0 494.2 -17.2 -36.4 206.3 2.3 16.8 16.0 59.6 5962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.9 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 419.2 -27.6 -39.0 311.1 2.3 32.4 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>									
16.0 \$9.6 \$962.2 486.2 -18.0 -36.9 187.4 2.2 17.1 16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 419.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.1 33.2 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>									
16.5 60.6 6086.1 478.2 -18.8 -36.5 172.1 2.2 19.3 17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>									
17.0 61.8 6230.4 469.0 -20.2 -34.4 162.4 1.8 26.9 17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>									
17.5 63.0 6389.6 459.0 -21.6 -34.1 174.7 .7 31.0 18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 396.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 <		_							
18.0 64.0 6502.6 452.0 -22.8 -35.1 129.4 .2 31.3 18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 396.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0									
18.5 65.3 6666.5 442.0 -24.0 -35.6 58.5 .7 33.2 19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 386.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0				-					
19.0 66.4 6812.8 433.2 -25.5 -36.9 359.1 1.3 33.5 19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 386.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0									
19.5 67.4 6937.6 425.8 -26.7 -38.1 331.1 2.0 32.7 20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 396.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0									
20.0 68.4 7067.4 418.2 -27.6 -39.0 311.1 2.3 32.4 20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.0 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 396.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0									
20.5 69.5 7200.7 410.5 -28.9 -40.1 294.7 2.4 32.9 21.0 70.6 7335.9 402.8 -30.8 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 386.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0									
21.0 70.6 7335.9 402.8 -30.8 -40.9 282.7 2.1 33.2 21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 386.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0									
21.5 71.8 7479.4 394.8 -30.9 -41.7 266.9 1.5 33.4 22.0 73.0 7637.8 386.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0									
22.0 73.0 7637.8 386.0 -32.5 -43.1 233.1 .9 33.5 22.5 74.2 7792.7 377.6 -33.8 -44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0		-							
22.5 74.2 7792.7 377.6 ~33.8 ~44.3 229.5 .9 33.7 23.0 75.2 7923.5 370.6 ~35.0 ~45.3 222.3 .9 34.0		-							
23.0 75.2 7923.5 370.6 -35.0 -45.3 222.3 .9 34.0								. 9	
								. 9	34.0
23.5 76.2 8056.2 363.6 -36.4 -46.4 211.5 .9 34.3							211.5		
24.0 77.2 8190,7 356.6 -37.5 -47.3 218.9 1.0 34.6	24.0	77.2			-37.5	~47.3		1.0	
24.5 78.2 8323.2 349.8 -38.7 -48.3 243.4 f.1 35.1	24.5	78.2		349.8	-38.7	-48.3	243.4	1.1	35.1

14 APRIL 1981 1541 GHT

TIME	CHTCT	HEIGHT	PRES	TEMP	DEU PT	DIR	SPEED H/SEC	R HUM PCT
MIH		GPH	ND .	DG C	DG C	265.5		999.9
25.0	79.2	0445.0	343.6	-39.9	99.9	263.3	1.5 2.8	999.9
25.5	80.2	6562.6	336.0	-40.9	99.9 99.9	295.4	2.1	999.9
26.0	81.2	0700.1	330.6	-42.1 -43.3	99.9	306.0	2,1	999.9
26.5	62.2	9046.4	323.0	-44.5	99.9	312.5	2.3	222.2
27.0	63.2	0974.0	317.8 311.6	-45.4	99.9	314.2	2.3	999.9
27.5 28.0	84.2	91 05 . 0	304.8	-46.7	99.9	314.6	2.3	999.9
28.5	65 .2	9252.5 93 8 4.1	298.8	-47.7	99 .9	313.9	2.6	999.9
29.0	97.3	9530.3	292.3	-48.7	99.9	312.3	2.9	999.9
29.5	88.4	9695.0	265.0	-49.7	99.9	309.3	3.9	999.9
30.0	89.4	9029.6	279.2	-50.4	99.9	304.4	5.2	999.9
30.5	90.4	9975.7	273.0	-51.2	99 .9	299.7	6.7	999.9
					99 .9	297.1	8.1	999.9
31.0	91.4	10105.4	267.6	-52.1 -52.9	99.9	296.2	9.2	999.9
31.5	92.4	10242.0	262.0		99.9	295.5	9.9	999.9
32.0	93.4	10376.1	256.6	-54.1 -55.2	99.9	293.9	10.0	999.9
32.5	94.4	10517.3	251.0		99.9	290.6	10.2	999.9
33.0	95.4	19656.0	245.6	-55.9				999.9
33.5	96.4	16002.4	240.0	-56.9	99.9 99.9	287.0 285.9	11.4 13.5	999.9
34.0	97.4	10946.4	234.6	-57.8	99.9	286.8	15.2	999.9
34.5	98.4	11967.3	229.4	-58.6	99.9	287.1	15.5	999.9
35.0	99.4	11220.4	224.6	-58.9	99.9	285.9	14.4	999.9
35.5	100.3	11369.1	219.3	-59.0	99.9	282.9	12.6	999.9
36.0	101.2	11489.2	215.2	-59.2	99.9	277.3	11.2	999.9
36.5	102.0	11611.5	211.0	-59.6	99.9	271.6	11.1	999.9
37.0	103.0	11761.6	206.0	-59.3		271.6	12.2	999.9
37. 5	104.0	11915.2	201.0	-60.2	99.9	274.5	13.1	999.9
30.0	105.0	12040.4	197.0	-60.9	99 .9		13.1	999.9
38.5	106.0	12200.3	192.0	-60.7	99.9	273.8	12.9	999.9
39.0	1 06 . 8	12337.4	187.8	-60.1	99.9	267.8		999.9
39.5	107.8	12472.8	183.8	-60.0	99.9	259.7	13.1	•
40.0	108.7	12615.4	179.7	-59.3	99.9	255.2	13.8	999.9 999.9
40.5	109.6	12759 . 1	175.6	-58.1	99.9	255.8	14.7 15.2	999.9
41.0	110.6	12926.9	171.0	-57.4	99.9	256.5	15.2	999.9
41.5	111.5	13076.2	167.0	-57.5	99.9	258.4	14.8	999.9
42.0	112.3	13216.6	163.3	-57.9	99.9	255.9 252.2	14.2	999.9
42.5	113.2	13372.5	159.3	-58.1	99.9	247.2	13.5	999.9
43.0	114.0	13505.4	156.0	-58.1	99.9		13.5	777.7
43.5	115.0	13669.2	152.0	-57.7	99.9	239.7	14.3	999.9
44.0	115.8	13809.3	148.7	-57.9	99.9	235.0 234.2	15.2	999.9
44.5	116.7	13952.3	145.3	-58.5	99.9		16.4	999.9
45.0	117.5	14075.8	142.5	-58.9	99.9	236.2		999.9
45.5	118.4	14214.1	139.4	-59.0	99.9	239.6	17.8	999.9
46 . 0	119.3	14384.5	135.7	-58.7	99 .9	242.8	18.3	
46.5	120.2	14540.6	132.3	-58.6	99.9	244.7	17.9	999.9
47.0	121.0	14700.5	129.0	-50.0	99.9	244.6	16.7	999.9
47.5	121.0	14865.3	125.7	-58.8	99.9	242.1	16.4	999.9
40.0	122.7	15000.0	123.0	-50.6	99.9	240.5	17.5	999.9
40.5	123.5	15155.0	120.0	-58.4	99.9	241.3	10.6	999.9
49.0	124.3	15314.6	117.0	-38.2	99.9	244.0	18.9	999.9
49.5	125.2	15459.9	114.3	-50.2	99.9	247.2	18.0	999.9
50.0	126.0	15645.7	111.0	-58.1	99.9	248.2	16.2	999.9
50.5	126.8	15789.3	188.5	-50.6	99 .9	244.7	15.1	999,9

ŧ.

The second second

51.0	127.6	15919.0	106.3	-58.9				
		10919.0	106.3		99.9	242.3	15.4	999.9
51.5	128.3	16076.1	103.7	-58.9	99.9	240.8	15.4	999.9
52.0	129.2	16270.0	100.5	-59.1	99.9	238.9	14.2	999,9
52.5	130.0	16427.2	98.0	-60.2	99,9	232.0	12.1	999.9
53.0	130.7	16565.5	95.9	-60.8	99.9	223.5	12.6	999.9
53.5	131.5	16720.5	93.5	-61.0	99.9	219.6	13.4	999.9
54.0	132.3	16888.8	91.0	-61.0			13,4	
54.5					99.9	218.9	14.2	999.9
	133.1	17056.7	99.6	-60.9	99.9	218.4	14.9	999.9
55.0	133.9	17209.0	86.4	-60.9	99.9	216.8	16.6	999.9
55.5	134.6	17365.6	84.3	-60.8	99.9	218.7	10.0	999.9
56.0	135.3	17526.0	82.1	-60.2	99.9	222.3	19.1	999.9
56.5	136.0	17690.4	80.0	-58.9		228.5	16.7	999.9
57.0	136.7	17861.9	77.9	-58.6	99.9	231.4	14.0	999.9
57.5	137.5	18013.4	76.0	-58.1	99,9			
58.0	138.3		74.1	-30.1			13.0	999.9
		18169.6		-58.2	99.9	236.6	14.0	999.9
58.5	139.0	18352.9	72.0	-59.3	99.9	240.7	16.6	999.9
59.0	139.7	18609.8	69,1	-57.9	99.9	246.4	13.5	999.9
59.5	140.4	18747.8	67.6	-57.2	99 .9	247.8	10.2	999.9
60.0	141.0	18806.4	67.0	-56.7	99.9	242.7	6.6	999.9
60.5	141.7	19014.2	64.9	-56.1	99.9		7.6	999.9
61.0	142.4	19211.6	62.9	-56.3	99.9			
61.5						214.1	8.2	999.9
	143.0	19402.1	61.0	-56.9	99.9		8.4	999.9
62.0	143.6	19601.9		-56.7	99.9	202.6	7.2	999.9
62.5	144.2	19771.2	57.6	-56.7	99.9		6.4	999.9
63.0	144 8	19894.8	56.4	-57.0	99 .9	195.1	6.1	999.9
63.5	145.4	20030.6	55.2	-57.0	99.9	196.6	6.6	999.9
64.0	146.0	20174.5	54.0	-56.9	99.9	200.3	7.7	999.9
64.5	146.6	20375.4	52.3	-57.2	99.9	208.0	7.2	999.9
65.0	147.1	20564.2	50.8	-57.4	99.9	217.9	6.9	999.9
65.5	147.7	20704.8	49.7	-57.2	99.9			
						234.6	6.7	999.9
66.0	148.2	20878.1	48.3	-57.0	99.9	245.7	6.1	999.9
66.5	148.8	21100.3 21273.8	46.7	-56.9	99.9	250.4	4.4	999.9
67.0	149.3	21273.8	45.4	-56.8	99.9	226.2	2.6	999.9
67.5	149.8	21414.7	44.4	-56.5	99.9	160.1	3.1	999.9
68.0	15ú.3	21605.1	43.1	-56.9	99.9	149.4	4.1	999.9
68.5	15ù.8	21828.4	41.6	-57.7	99.9	153.7	4.1	999.9
69.0	151.3	22012.5	40.4	-57.8	99.9	155.8	2.7	999.9
69.5	151.8	22170.4	39.4	-57.3	99.9			
70.0				-56.7		162.6	. 4	999.9
	152.3	22333.8	38.4		99.9	.3 5.9	2.1	999.9
70.5	152.8	22500.9	37.4	-56.0	99.9		4.9	999.9
71.0	153.3	22664.9	36 . 5	-55.0	99.9	18.2	5.9	999.9
71.5	153.7	22826.8	35.5	~53.7	99.9	36.9	6.3	999.9
72.0	154.2	23012.6	34.5	-53.1	99.9	48.0	6.9	999.9
72.5	154.5	23234.1	33.4	-53.8	99.9	51.1	7.2	999.9
73.0	154.9	23455.6		-54.5	99.9	53.9	7.6	999.9
73.5	155.3	23627.2	31.4	-54.5	99.9	48.0	8.3	999.9
74.0	155.7	23786.2	30.6	-54.3				
					99.9	41.4	9.3	999.9
74.5	156.1	23965.6	29.8	-54.1	99.9	37.5	10.1	999.9
75.0	156.5	24225.9		-53.8	99 .9	40.3	10.4	999.9
75.5	156.8	24486.3	27.5	-53.6	9 9.9	42.9	10.6	999.9
76.0	157.2	24689.9	26.6	-53.1	99.9	45.3	11.0	999.9
76.5	157.5	24855.6	25.9	-52.5	99.9	47.4	11.4	999.9
77.0	157.9	25021.4	25.3	-51.9	99.9	49.3	11.6	999.9
77.5	159.2	25178.1	24.7	-51.4	99.9	46.7	11.8	999.9
78.0	158.4	25328.8	24.1	-51.1	99.9	41.0	11.5	999.9
78.5	158.7	25479.5	23.6	-50.8	99.9			
79.0						35.0	11.4	999.9
	159.0	25630.2	23.0	-50.4	99.9	28.9	11.3	999.9
79.5	159.3	25864 . 2	22.2	-50.0	99.9	29.6	11.4	999.9
80.0	159.6	26130.3	21.3	-49.7	99.9	30.3	11.4	999.9
80.5	159.8	26392.3	20.5	-49.3	99.9	31.0	11.5	999.9

81.0	160.1	26651.9	19.7	-48.9	99.9	30.5	11.7	999.9
								999.9
81.5	160.4	26919.6	19.0	-48.5	99.9	20.4	12.2	
82.0	160.6	27187.3	10.2	-48.0	99.9	26.5	12.8	999.9
82.5	160.9	27455.0	17.5	-47.6	99.9	24.0	13.3	??? .?
83.0	161.1	27688.4	16.8	-46.9	99.9	24.6	13.1	999.9
83.5	161.3	27876.2	16.4	-45.9	99.9	27.0	11.9	999.9
84.0	161.5	28052.0	16.0	-44.9	99.9	29.9	10.7	999.9
84.5	161.7	28233.8	15.5	-44.0	99.9	33.4	9.5	999.9
85.0	162.0	28415.6	15.1	-43.0	99.9	38.0	8.4	999.9
85.5	162.1	26590.0	14.7	-42.7	99.9	999.9	99.9	999.9
86.0	162.3	28762.6	14.4	-42.6	99.9	999.9	99.9	999.9
86.5	162.5	28935.2	14.0	-42.6	99.9	999.9	99.9	999.9
87.0	162.7	29107.8	13.6	-42.5	99.9	999.9	**.	999.9
97 8	162 9	29280 4	13.3	-49.4	99.9	999.9	99.9	222.2

大大 一大大大大大

STATION NO. 2 UNEELER RIDGE, CALIF

						14	APRIL 1815 GI	1981 4T
TIME	CHTCT	HEIGHT	PRES	TENP	DEW PT	DIR	SPEED	R HUN
HIH		GPM	HB	DG C	DG C	DG	H/SEC	PCT
0.0	6.8	168.0	1002.0	22.6	0 .0	330.0	. 5	39.0
. 5	7 . 6	246.2	993.0	20.7	7.7	284.4	. 6	42.9
1.0	9.0	368.5	979.0	19.2	6.6	280.9	. 9	44.0
1.5	10.5	514.3	962.5	17.5	5.7	289.2	. 8	46.0
2.0	11.8	630.2	949.5	16.5	4.9	275.0	. 3	46.3
2.5	13.0	751.8	936.0	15.4	4.2	198.2	. 6	47.0
3.0	14.3	973.5	922.7	14.9	4.7	152.4	. 3	50.4
3.5	15.8	1004.4	908.5	14.4	4.3	114.5	.2	50.6
4.0	17.0	1121.3	896.0	13.9	3.9	194.9	2.2	50.9
4.5 5.0	18.7	1286.1	878.7	13.7	3.7	155.4	4.4	50.7
5. U	20.0 21.5	1418.5 1561.9	865.0 850.5	15.9 15.2	2.5 -7.0	132.8 134.7	7.2 9.2	40.7 20.8
6.0	22.8	1681.9	838. 5	14.1	~7.5	133.7	7.9	21.6
6.5	24.0	1808.2	92 6.0	13.1	-7.6	131.3	7.3	22.9
7.0	25.3	1936.1	813.5	12.2	-7.7	126.9	7.9	24.1
7.5	26.5	2065.6	801.Ú	11.2	-8.0	126.1	8.3	25.2
8.0	27.6	2180.7	790.0	9.9	-8.4	126.6	8.5	26.7
6.5	28.8	2302.2	776.5	9.0	-0.3	125.5	8.7	20.5
9.0	30.0	2485.0	767.0	7.5	-9.0	126.5	8.7	29.7
9.5	31.0	2533.0	757.0	7.3	-8. š	126.5	9.1	31.8
10.0	32.3	2666.9	744.8	5.6	-9.9	127.6	9.2	31.7
10.5	33.4	2785.6	734.0	4.4	-11.1	130.0	8.7	31.5
11.0	34.4	2892.6	724.4	3.5	-12.1	135.5	8.5	30.8
11.5	35.5	3004.1	714.5	3.0	-13.7	143.6	9.1	28.0
12.0	36.8	3141.1	702.5	2.4	-14.6	151.8	10.1	27.2
12.5	38.0	3274.1	691.0	1.4	-16.0	160.6	9.9	25.9
13.0	39.0	3379.5	682.0	. 7	-18.8	167.3	8.4	21.4
13.5	40.3	3516.1	676.5	.4	-22.0	166.3	7.1	16.7
14.0	41.4	3644.9	659.8	5	-23.2	164.2	5.7	16.0
14.5	42.4	3747.1	651.4	-1.6	-24.1	161.5	4.9	16.0
15.0	43.5	3868.7	641.5	-2.6	-25.0	156.0	4.4	15.9
15.5	44.6	3991.8	631.6	-3.6	-25.9	152.0	4.3	15.8
16.0	45.8	4122.0	621.3	-4.6	-26.7	147.9	4.6	15.8
16.5	46.8	4242.6	611.8	-5.0	-27.0	152.1	5.2	15.8
17.0	47.8	4358.9	602.8	-5.4	-27.4	159.9	5.9	15.8
17.5	49.0	4500.4	592.0	-6.1	-27.5	168.6	6.0	16.4
18.0	50.3	4637.0	581.8	-7.0	-27.8	179.1	5.1	17.0
18.5	51.4	4771.4	571.8	-7.7	-26.2	191.8	4.4	17.5
19.0	52.4	4886.4	563.4	-8.3	-28.5	202.5	4.3	17.6
19.5	53.5	5016.8	554.0	-9.1	-29.2	207.7	4.7	17.7
20.0	54.6	5140.5	545.2	-10.0	-29.9	208.5	5.0	17.7
20.5	55.6	5262.9	536.6	-11.2	-30.5	206.5	4.9	18.4
21.0	56.6	5383.7	528.2	-12.4	-31.0	204.1	4.5	19.3
21.5	57.6	5500.1	520.2	-13.5	-31.7	203.8	4.1	19.6
22.0	58.6	5635.5	511.0	-14.6	-32.8	205.6	3.8	19.4
22.5	59.8	5760.9	502.6	-15.4	-33.5	204.8	3.4	19.4
23.0	60.8	5881.7	494.6	-16.8	-34 . 7	196.6	3.3	19.4
23.5	61.8	6004.0	486.6	-17.7	-35.4	187.8	3.3	19.5
24.0	63.0	6152.8	477.0	-18.5	-33.9	184.4	2.6	24.0
24.5	64.0	6278.7	469.0	-19.7	-33.2	191.2	1.4	28.7

STATION NO. 2 WHEELER RIDGE, CALIF

						14	APRIL 1915 G	1981 HT
TIME	CHICT	HEIGHT	PRES	TEMP	DEU PT	DIR	SPEED	R HUM
MIH		GPM	MB	DG C	DG C	DG	H/SEC	PCT
25.0	65.0	6406.1	461.0	-21.0	-34 . 5	183.7	1.4	28.3
25.5	66.2	6558 . 1	451.6	-22.1	-35.6	195.8	1.0	27.4
26.0	67.2	6676.1	444.4	-23.3	-36.6	226.2	. 6	28.1
26.5	69.2	6805.3	436.6	-24.6	-37.6	265.1	.5	20.0
27.0 27.5	69.2 70.2	6926.1 7058.4	429.4 421.6	-26.1 -27.3	-36.3 -30.5	294.1	. 0	30.3
28.0	71.2	7178.7	414.6	-28.4	-39.5 -40.1	305.2 308.9	1.2	30.3
28.5	72.2	7300.6	407.6	-29.6	-41.0	292.1	1.4 .	31.1 31.7
29.0	73.3	7434.7	400.0	-30.6	-41.8	219.9	1.0	32.2
29.5	74.4	7592.4	391.2	-31.8	-42.7	216.6	1.8	32.6
30.0	75.4	7719.8	784.2	-32.5	-43.6	229.2	2.6	31.6
30.5	76.4	7849.3	377.2	-33.3	-44.3	238.4	3.2	31.7
31.0	77.5	7993.8	369.5	-34.5	-45.3	245.3	3.6	31.0
31.5	78.6	6129.1	362.4	-35.8	-46.5	253.5	3.7	31.9
32.0	79.6	8 256.6	355.8	-37.0	-47.6	260.8	3.6	32.0
32.5	80.6	8393.7	348.8	-38.3	-48.6	266.0	3.2	32.3
33.0	81.6	6520.7	342.4	-39.6	99.9	266.2	3.0	999.9
33.5	82.6	8653.6	335.0	-40.7	99.9	261.0	3.2	999.9
34.0	83.6	8784.3	329.4	-41.6	99.9	257.5	3.6	999.9
34. 5 35.0	84.6	8921.4	322.8	-42.7	99.9	261.1	4.3	999.9
35.0 3 5 .5	85.6 86. 5	9056.2 9171.6	316.4 311.0	-42.9 -44.6	99.9 99.9	267.9	5.2 6.1	999.9
36.0	87.4	9288.7	305.6	-45.3	99.9	268.5 263.5	6.8	999.9 999.9
36.5	88.4	9429.7	299.2	-46.4	99.9	256.8	7.4	999.9
37.0	89.4	9577.5	292.6	-47.4	99.9	254.0	7.8	999.9
37.5	90.4	9714.1	296.6	-48.6	99.9	255.2	8.0	999.9
38.0	91.5	9855.2	290.5	-49.0	99.9	259.1	9.2	999.9
38.5	92.5	9984.6	275.0	-50.7	99 .9	264.8	8.5	999.9
39.0	93.4	10113.6	269.6	-51.5	99.9	271.6	9.0	999.9
39.5	94 . 4	10259.4	263.6	-52.5	99.9	279.4	9.5	999.9
40.0	95 . 4	10397.8	258.0	-53.5	99 .9	286.0	9.7	999.9
40.5	96.4	10533.7	252.6	-54.4	99.9	200.6	9.6	999.9
41.0	97.3	10668.3	247.3	-55.3	99.9	200.3	9.4	999.9
41.5	98.2	10786.2	242.6	-55.9	99.9	288.1	9.3	999.9
42.0	99.2	10935.3	237.2	-56.6	99.9	290.4	9.3	999.9
42.5 43.0	100 0 101.0	11047.3 11212.0	233.0 227.0	-57.4 -57.9	99.9 99.9	291.1	9.6	999.9
43.5	101.8	11212.0	227.0	-57.9 -58.6	99.9 99.9	285.0 275.2	9.9 10. 9	999.9 999.9
44.0	102.0	11489.7	217.2	-59.2	99.9	269.2	12.3	999.9
44.5	103.8	11641.4	212.0	-59.4	99.9	270.9	13.1	999.9
45 0	104.8	11790.7	207.0	-59.7	99.9	277.4	12.9	999.9
45.5	105.7	11902.4	203.3	-59.8	99.9	281.4	11.7	999.9
46.0	106.6	12037.0	199.0	-60.3	99.9	278.4	10.2	999.9
46 . 5	107.6	12195.5	194.0	-60.8	99.9	266.1	9.7	999.9
47.0	108.6	12358.0	189.0	-60.5	99.9	254.6	10.7	999.9
47.5	109.6	12504.8	184.6	-59.8	99.9	249.3	11.8	999.9
48.0	110.6	12662.9	180,0	-59.5	99.9	247.3	11.9	999.9
48.5	111.6	12817.6	175.6	-59.6	99.9	246.2	11.9	999.9
49.0	112.5	12965.7	171.5	-59.4	99.9	244.5	12.2	999.9
49.5	113.4	13117.3	167.4	-58.6	99.9	242.5	12.5	999.9

ORIGINAL PAGE IS OF POOR QUALITY

STATION NO. 2 WHEELER RIDGE, CALIF

						14	APRIL	1981
							1815 G	MT
TIME	CHTCT	HEIGHT	PRES	TEMP	DEW PT	DIR	SPEED	R HUH
MIN		GPH	MB	DG C	DG C	DG	M/SEC	PCT
50.0	114.4	13269.6	163.4	-57.7	99.9	240.6	12.5	999.9
50.5	115.4	13426.2	159.4	-57.3	99.9	239.7	12.5	999.9
51.0	116.3	13576.1	155.7	-57.0	99.9	240.0	12.7	999.9
51.5	117.2	13712.9	152.3	-57.4	99.9	241.0	12.9	999.9
52.0	118.0	13052.4	149.0	-57.6	99.9	241.6	12.7	999.9
52.5	118.8	13995.6	145.7	-57.4	99.9	239.0	12.8	999.9
53.0	119.8	14165.6	141.8	-57.7	99.9	234.8	13.3	999.9
53.5	120.7	14322.0	136.3	-57.7	99.9	230.8	14.3	999.9
54.0	121.6	14494.6	134.6	-58.0	99.9	226.9	15.2	999.9
54.5 55.0	122.6	14684.6	130.6	-58.2	99.9	229.6	15.6	999.9
55.5	123.5 124.3	14835.4	127.5	-58.8	99.9	231.9	15.4	999.9
56.0	125.1	14976.8 15134.3	124.7 121.6	-58.9 -58.1	99.9 99.9	233.0	14.6	999.9
56.5	125.9	15246.5	119.4	-57.5	99.9	233.8 230.4	13.6 13.8	999.9 999.9
57.0	126.7	15413.0	116.3	-57.4	99.9	226.1	15.6	999.9
57.5	127.6	15585.4	113.2	-57.0	99.9	226.3	16.5	777.7
50.0	128.4	15726.2	110.7	-56.5	99.9	230.4	16.1	999.9
50.5	129.2	15044.2	108.3	-56.2	99.9	232.7	15.5	999.9
59.0	130.0	1600.0	105.0	-56.7	99.9	234.0	14.7	999.9
59.5	130.8	16215.2	102.5	-56.7	99.9	232.0	12.8	999.9
60.0	131.7	16371.8	100.0	-57.2	99.9	226.6	11.6	999.9
60.5	132.4	16518.0	97.7	-57.7	99.9	221.5	11.6	999.9
61.0	133.2	16662.1	95.5	-58.4	99.9	218.8	12.3	999.9
61.5	134.0	16020.1	93.0	-59.8	99.9	220.4	13.8	999.9
62.0	1'4.7	16974.1	90.9	-60.6	99 .9	223.8	15.5	999.9
62.5	135.5	17137.9	88.5	-60.9	99.9	227.7	15.9	999.9
63.0	136.3	17305.8	96 . 1	-60.7	99.9	232.1	14.8	999.9
63.5	137.0	17461.9	84.0	-60.2	99.9	237.3	12.6	999.9
64.0	137.7	17624.3	81.9	-59.7	99.9	237.3	12.2	999.9
64.5	130.5	17807.2	79.5	-59.6	99.9	239.5	11.7	999.9
65.0	139.3	17986.7	77.3	-59.4 -58.4	99.9	244.2	10.5	999.9
65.5 66.0	139.9 140.6	18140.5 18318.1	75.4 73.3	-58.1	99.9 99.9	251.9 251.0	8.7 6.2	999.9 999.9
66.5	141.3	18479.3	71.4	-57.5	99.9	237.9	4.3	999.9
67.0	142.0	18606.6	70.0	-56.1	99.9	212.6	4.3	999.9
67.5	142.6	18780.6	68.1	-56.2	99.9	208.0	6.1	999.9
68.0	143.3	18957.8	66.3	-56.3	99.9	206.5	7.7	999.9
68.5	143.9	19139.6	64.4	-56.4	99.9	206.6	9.1	999.9
69.0	144.6	19291.1	62.9	-56.6	99.9	200.4	9.5	999.9
69.5	145.2	19447.1	61.3	-57.0	99.9	209.5	8.9	999.9
70.0	145.6	19621.4	59.7	-57.5	99.9	208.5	7.1	999.9
70.5	146.4	19772.9	58.2	-57.4	99.9	210.1	6.4	999.9
71.0	147.0	19909.1	57.0	-56.9	99.9	213.7	6.5	999.9
71.5	147.6	20123.3	55 · 1	-56.8	99.9	224.6	5.4	999.9
72.0	148.2	20304.9	53.6	-56.8	99.9	234.9	4.2	999.9
72.5	143.8	20437.7	52.4	-56.9	95.5	242.4	2.7	999.9
73.0	149.3	20603.7	51.1	-57.0	99.9	225.5	1.9	999.9
73.5	149.8	20791.7	49.6	-57.3	99.9	169.9	2.3	999.9
74.0	150.3	20946.2	48.4	-56.9	99.9	155.2	2.2	999.9
74.5	150.	21078.4	47.4	-56.1	99.9	108.1	2.6	999.9

STATION NO. 2 WHEELER RIDGE, CALIF

						14	APRIL	1981
							1815 C	MT
TIME	CHTCT	HE I GHT	PRES	TEMP	DEW PT	DIR	SPEED	R HUH
HIH		GPH	HB	DG C	DG C	DG	H/SEC	PCT
75.0	151.3	21214.3	46.4	-55.8	99.9	102.3	2.4	999.9
75.5	151.0	21352.6	45.4	-56.0	99.9	126.5	1.3	999.9
76.0	152.3	21539.7	44.1	-56.0	99.9	164.6	. 7	999.9
76.5	152.8	21759.2	42.6	-55.8	99.9	249.7	. 5	999.9
77.0	153.3	21975.5	41.2	-36.0	99.9	106.6	1.4	999.9
77.5	153.7	22189.6	39.0	-56.3	99.9	102.4	4.5	999.9
78.0	154.2	22379.0	30.6	-56.2	3 9.9	96.5	7.5	999.9
70.5	154.6	22531.4	37.7	-55.4	99.9	85.7	8.7	999.9
79.0	155.1	22707.6	36.7	-54.7	99.9	76.1	9.3	999.9
79.5	155.6	22978.4	35.2	-54.4	99 .9	54.0	7.0	999.9
80.0	156.1	23227.5	33.6	-54.1	99.9	30.5	6.5	777.7
60.5	156.5	23309.0	33.0	-53.9	99.9	41.9	7.1	999.9
81.0	156.9	23552.0	32.2	-53.7	99.9	51.1	Ø. 1	999.9
81.5		23695.0	31.5	-52.9	99.9	50.5	€.3	999.9
82.0	157.6	23935.1	30.8	-51.9	99.9	47.9	0.5	999.9
82.5	157.9	23974.3	30.1	-50.9	99.9	45.3	0.6	999.9
83.0	158.3	24186.1	29.2	-50.1	99.9	46.7	0.9	999.9
83.5	159 6	24416.1	20.2	-49.4	99.9	40.9	9.3	999.9
84.0	158.9	24646.1	27.2	-48.6	? 9.9	51.0	9.7	999.9
84.5	159.3	24827.3	26.5	-48.4	99.9	52.7	16.6	999.9
95 .0	159.6	24996.2	25 . 8	-48.2	99.9	54.0	11.7	999.9
85.5		25165.2	25.1	-48.1	99.9	55.1	12.8	999.9
86.0	160.2	25397.7	24.3	-47.8	99.9	52.7	12.2	999.9
86.5		25646.1	23.4	-47.6	99.9	40.8	11.3	999.9
87.0	160.8	25894.5	22.5 21.8	-47.3	99.9	44.3	10.4	999.9
87.5	161.1	26106.2	21.9	-47.5	99.9	40.2	9.8 9.5	999.9
88.0	161.4	26262.8	21.3 20.8	-48.3	99.9	37.6	9.3	999.9 999.9
88.5	161 6	26419.4	20.8	-49.1	99.9	34,9 32.0	9.0	999.9
89.0	161.9	26576.0	20.3	-49.9 -50.6	99.9 99.9		9.7	999.9
89.5	162.1	26763.1	17.1				8.4	999.9
90.0	162.3	26996 - 0	19.1 18.4	-49.0	99.9 99.9	19.5 11.2	0.3	999.9
90.5	162.5	27229.0	17.8	-48.0 -47.0	99.9	2.8	9.3	999.9
91.0	162.7	27461.9			99.9	354.6	8.5	999.9
91.5	163.0	27694.8	17.1 16.6	-45.9 -45.2	99.9	349.6	8.7	222.2
92.0	163.1	27921.3				345.5	9.0	222.2
92.5	163.3	28146.3	16.1 15.6	-44.5 -43.8	99.9 99.9	345.5	9.3	999.5
93.0	163.5	28371.2	15.0	-43.8 -43.2	99.9	338.1	9.6	775.7
93.5	163.7 163.8	28596.1	14.5	-42.5	99.9	334.8	10.0	999.9
94.0 94.5	164.0	2 08 21.0 29045.9	14.0	-41.0	99.9	331.8	10.4	222.2
	164.2	29045.9 29286.3	13.5	-40.5	99.9	777.7	99.9	999.9
95.0 95.5	164.5	29526.6	13.1	-39.2	22.2	999.9	99.9	939.9
96.0	164.7		12.6	-37.9	99.9	999.9	99.9	999.9
96.5	164.9	30007.3	12.2	-36.6	99.9	997.9	99.9	999.9
70.3	187.7	9446.9						

14	APRIL	1981
	1818 GMT	

TIME	CHTCT	HEIGHT	PRES	TEMP	DEW PT	DIR	SPEED	R HUM
MIG	CITTOT	GPM	MB	DG C	DG C	DG	M/SEC	PCT
0.0	20.0	1366.0	867.8	21.0	2.3	150.0	6.2	29.0
.5	21.7	1540.6	850.3	17.4	-4.7	113.8	6.6	21.7
1.0	24.0	1775.9	827.0	13.3	-8.0	106.6	6.3	21.9
1.5	25.7	1936.3	811.3	11.8	-7.6	112.9	6.9	24.9
2.0	27.4	2112.1	794.4	10.1	-7.5	119.7	8.0	28.0
2.5	29.0	2274.3	779.0	8.9	-8.1	117.9	9.1	28.9
3.0	30.7	2456.5	762.0	7.3	-8.6	117.1	10.4	31.3
3.5	32.3	2630.5	746.0	5.4	-8.7	117.4	11.2	35.3
4.0	34.0	2807.1	730.0	3.9	-9.2	114.0	11.9	37.9
4.5	35.7	2982 9	714 3	2.0	-9.5	112.3	11.1	42.0
5.0	37.0	3111.6	703.0	7.7	-10.8	112.1	10.8	41.5
5,5	38.5	3273.1	689.0	1	-18.0	124.0	9.4	25.3
6.0	39.8	3401.7	678.0	-,4	-20.8	141.8	8.6	19.5
6.5	41.3	3580.2	663.0	-1.6	-21.2	149.2	9.5	20.8
7.0	43.0	3749.8	649.0	-2.0	-23.9	153.0	9.6	16.7
7.5	44.3	3898.0	637.0	-3.0	-24,2	158.3	9.2	17.5
8.0	45.8	4057.7	624.3	-4.3	-25.3	163.0	8.9	17.5
8.5	47.3	4234.8	610.3	-5.6	-27.2	170.4	7.7	16.3
9.0	48.8	4391.4	598.3	-6.4	-27.9	177.3	6.3	16.2
9.5	50.5	4586 . 2	593.5	-7.3	-28.4	186.9	4.6	16.5
10.0	51.8	4727.3	573.0	-8.5	-29.1	199.9	3.4	17.0
10.5	53.3	4904.7	560.0	-10.1	-30.5	206.6	3.0	17.0
11.0	54.5	5043.3	550.0	-11.3	-31.5	204.6	3.3	16.9
11.5	56.0	5226.2	537.0	-12.5	-32.7	199.3	3.9	16.6
12.0	57.3	5369.7	527.0	-13.3	-32.5	206.8	3.9	18.0
12.5	58.5	5515.2	517.0	-14.6	-33.3	212.3	4.0	18.4
13.0	59.8	5662.8	507.0	-15.9	-34.1	218.9	4.0	18.9
13,5	61.0	5812.4	497.0	-17.4	-35.0	220.8	3.9	19.8
14.0	62.3	5964.7	481.4	-18.1	-35.8	209.4	3.3	19.4
14.5	63.5	6111.6	477.5	-19.1	-36.4	197.9	2.8	19.9
15.0	64 8	6260.8	468.0	-20.6	-35.7	191.2	2.0	24.5
15.5	66.0	6420.1	458.0	-21.6	-34.4	200.1	.8	30.0
16.0	67.3	6561.9	449.3	-23.2	-35.1	318.8	.2	32.5
16.5	68.5	6714.0	440.0	-24.6	-35.5	347.0	, 5	35.1
17.0	64.8	6868.2	430.8	-26.0	-36.6	327.7	. 6	36.0
17.5	71.0	7033.3	421.0	-27.5	-38.0	302.6	1.0	35.9
18.0	72.3	7184.3	412.3	-28.5	-38.9	301.5	1.6	35.7
18.5	73.4	7325.4	404.2	-29.7	-40.0	290.6	1.8	35.6
19.0	74.5	7462.2	396.5	-30.9	-41.1	262.0	1.7	35.4
19.5	76.0	7651.8	386.0	-32.7	-42.8	235.9	2.2	35.1
20.0	77.3	7813.1	377.3	-34.0	-43.9	239.5	2.6	35.6
20.5	7Ŗ.4	7963 8	369.2	-35.5	-45.3	241.4	3.0	35.5
21.0	79.4	8096.8	362.2	-36.6	-46.3	244.0	3.5	35.4
21.5	80.5	8235.5	355.0	-37.7	-47.3	247.2	3.8	35.4
22.0	81.8	8397.2	346.8	-39.3	-48.8	251 3	3.9	35.3
22.5	83.3	8586.9	337.3	-40.7	99.9	258.8	3.7	999.9
23.0	84.5	8765.3	328.5	-42.4	99.9	265.6	3.7	999.9
23.5	85.6	8912.5	321.4	-43.6	99.9	262.7	4.0	999.9
24.0	86.8	9058 0	314.5	-44.9	99.9	255.2	4.5	999.9
24.5	88.0	9218.7	307.0	-46.3	99.9	253.5		999.9

STATION NO. 4 TEHACHAPI, CALIF

14	APRIL	1981
	1919 CMT	

TIME	CHTCT	HEIGHT	PRES	TEMP	DEW PT	DIR	SPEED	R HUM
HIN		GPM	HB	DG C	DG C	DG	H/SEC	PÇT
25.0	89.3	9405.2	298.5	-47.2	99.9	264.6	6.5	999.9
25.5	90.5	9573.3	291.0	-48.2	99.9	272.2	7.9	999.5
26.0	91.6	9724.1	284.4	-49.3	99.9	273.9	9.2	999.9
26.5	92.6	9863.6	278.4	-50.3	99.9	272.2	10.2	999.9
27.0	94.0	10062.7	270.0	-51.6	99.9	270.4	11.1	999.9
27.5	95 . 3	10238.9	262.8	-53.1	99.9	274.2	11.7	999.9
28.0	96.4	10391.4	256.6	-54.1	99.9	279.8	11.8	999.9
28.5	97 . 4	10532.6	251.0	-55,0	99 .9	205.5	11.8	999.9
29.0	98.5	10687.0	245.0	~55.9	99.9	288.2	11.9	999.9
29.5	99.8	10864.2	236.3	-56.9	99.9	286.7	12.0	999.9
30.0	101.3	11073.6	236.5	-57.3	99,5	263.3	11.4	999.9
30.5	102.5	11268.2	223.5	-58.1	9 9.9	279.4	9.9	999.9
31.0	103.8	11446.7	217.3	-58.3	99.9	274.7	8.8	999.9
31.5	105.0	11630.0	211.0	-58.4	99.9	271.5	8.5	999.9
32.0	106.0	11780.8	206.0	-58.6	99.9	270.1	9.0	999.9
32.5	107.3	11943.4	200.8	-58.6	99.9	267.8	10.0	999.9
33.0	1 08 . 5	12142.2	194.5	-58.8	99.9	266.4	12.0	999.9
33.5	109.6	12322.3	189.0	-58.9	99 .9	265.2	14.7	999.9
34.0	110.6	12470.0	184.6	-58.9	99.9	264.6	17.0	999.9
34.5	111.6	12628.6	180.0	-58. 9	99.9	263.6	17.4	999.9
35.0	* 12.6	12/83.6	175.6	-59.0	99,9	259.5	16.4	999.9
35.5	113.6	12950.4	171.0	-59.1	99.9	252.7	15.1	999.9
36.0	114.6	13113.7	166.6	-58.7	99.9	247.6	14.4	999.9
36.5	115.6	13266.6	162.6	-58.2	99.9	245.1	14.0	999.9
37.0	116.6	13423.5	158.6	-58.0	99.9	242.6	13.9	999.9
37.5	117.6	13584.4	154.6	-58.3	99.9	239.5	14.1	999.9
38.0	118.6	13749.4	150.6	-58.3	99.9	236.9	14.9	999.9
38.5	119.6	13919.0	146.6	-58.1	99.9	236.1	16.1	999.9
39.0	120.6	14093.2	142.6	-58.3	99.9	236.2	16.9	999.9
39.5	121.6	14272.1	138.6	-58.8	99.9	235.5	16.9	999.9
40.0	122.6	14427.6	135.2	-59.2	99.9	233.6	16.9	999. 9
40.5	123.5	14578.0	132.0	-59.4	99.9	232.1	17.5	999.9
41.0	124.3	14738.2	128.7	-59.2	99.9	231.2	18.1	999. 9
41.5	125.2	14894.1	125.5	-58.7	99.9	230.8	18.4	999.9
42.0	126.0	15020.3	123.6	-58.4	9 9.9	231.9	18.7	999.9
42.5	126.8	15194.3	119.7	-57.0	99 .9	234.5	17.7	999.9
43.0	127.7	15336.9	117.0	~57.1	99.9	234.5	16.3	999.9
43.5	128.5	15501.6	114.0	-57.5	99.9	231.5	15.7	999.9
44.0	129.4	15681.0	110.8	-57.6	99.9	227.3	16.2	999.9
44.5	130.3	15834.3	108.1	-57.4	99.9	225.6	17.6	999.9
45.0	131.0	15960.3	106.0	-57.4	99.9	226.3	19.0	999.9
45.5	131.8	16111.5	103.5	-57.4	99.9	228.8	19.9	999.9
46.0	132.7	16308.3	100.3	-57.9	99.9	229.8	19.8	999.9
46.5	133.6	16507.7	97.2	-58.7	99.9	228.9	18.7	999.9
47.0	134.5	16684.2	94.5	-59.9	99.9	225.5	17.3	999.9
47.5	135.3	16851.3	92.0	-60.7	99.9	221.1	16.6	995.9
48.0	136.1	17017.6	89.6	-60.6	99.9	217.9	17.1	999.9
48.5	136.9	17168.7	87.4	-59.5	99.9	218.3	19.2	999.9
49.0	137.7	17345,2	85.0	-59.7	99.9	221.5	20.4	999.9
49.5	138.6	17554.9	82.2	-59.6	99.9	225.8	18.8	999.9

				14	APRIL 1818 G	1981 IT	
THE	PRES	TEMP	DEW PT	DIR	SPEED	R HUH	
PH	HB	DG C	DG C	DG	H/SEC	PCT	
3.2	8 0.1	-58.8	99.9	229.9	14.6	999.9	
7.3	78.6	-50.3	99.9	233.0	11.3	999.9	

TIME NIN	CHTCT	HEIGHT GPH	PRES MB	T EMP DG C	DEW PT	DIR DG	SPEED H/SEC	R HUH PCT
50.0	139.4	17713.2	80.1	-58.8	99.9	229.9	14.8	999.9
50.5	140.1	17033.3	78.6	-50.3	99.9	233.0	11.3	999.9
51.0	140.8	17985.4	76.8	-58.4	99.9	233.6	11.4	999.9
51.5	141.4	18154.9	74.7	-58.7	99.9	238.5	12.6	999.9
52.0	142.1	18337.0	72.6	-59.0	99.9	244.8	14.0	999.9
52.5	142.9	10525.2	70.4	-50.7	99.9	249.4	12.9	999.9
53 .0	143.6	18667.0	68.9	-58.4	99.9	241.9	11.1	999.9
53.5	144.3	1 00 26.5	67.1	-50.0	99 .9	220.6	9.8	999.9
54.0	145.0	19029.9	65.0	-57.2	99.9	215.2	9.6	999.9
54.5	145.7	19171.2	63.6	-57.0	99.9	212.7	9.8	999.9
55.0	146.4	19343.4	61.9	-57.1	99.9	210.5	9.7	999.9
55.5	147.0	19536 . 4	60.0	-57.4	99.9	200.3	9.5	999.9
56.0	147.6	19674.3	58.8	-57.4	99.9	212.1	8.9	999.9
56.5	148.3	19034.5	57.3	-57.5	99.9	216.3	8.4	999.9
57.0	148.9	20044.1	55.4	-57.7	99.9	221.1	7.9	999.9
57.5	149.5	20202.8	54.0	-57.9	99 .9	223.4	7.8	999.9
58.0	150.1	20365.4	52.6	-50.2	99.9	225.6	7.8	799.9
50.5	150.8	20594.4	50.7	-58.6	99.9	229.5	7.7	99919
59.0	151.3	20771.6	49.3	-58.6	99.9	229.3	5.8	999.9
59.5	151.9	20914.1	40.2	-50.5	99.9	221.6	2.6	999,9
60.0	152.4	21658.2	47.2	-57.6	99.9	200.2	2.6	999.9
60.5	152.9	21184.7	46.2	-56.6	99.9	199.6	3.1	999.9
61.0	153.5	21425.4	44.5	-56.7	99.9	195.1	3.5	999.9
61.5	154.1	21669.5	42.8	-56 . 8	99.9	188.5	3.5	999.9
62.0	154.6	21 8 28.8	41.8	-56.2	99.9	153.0	2.3	999.9
62.5	155.1	21978.7	40.8	-55.6	99.9	104.8	2.3	999.9
63.0	155.5	22115.2	39.9	-56 . 1	99.9	55 · 1	2.1	999.9
63.5	156.0	22259.8	39.0	-56.4	99.9	23.1	3.3	959.9
64.0	156.5	22491.8	37.6	-55.5	99.9	50.9	4.8	999.9
64.5	156.9	22723.8	36.3	-54.6	99.9	63.6	7.0	999.9
65.0	157.4	22903.5	35.3	-54.3	99.9	76.0	6.6	999.9
65.5	157.0	23678.1	34.4	-54.2	99.9	92.6	6.0	999.9
66.0	158.3	23290.6	33.2	-53.9	99.9	86.7	5.9	999.9
66.5	158.7	23568.5	31.8	-53.6	99.9	66.5	6.6	999:9
67.0	159.1	23766.1	30.7	-52.6	99.9	58.4	7.7	999.9
67.5	159.5	23932.5	30.1	-51.6	99.9	61.6	9.6	999.9
68.0	159.8	24076.9	29.4	-50.3 -49.4	99.9	64.2	9.5	99919
60.5	160.1 160.5	24 26 5. 0 24521.6	20.6 27.5	-49.2	99.9 99.9	64.8 63.1	10.2	999.9
69.0 69.5	160.9	24777.4	26.4	-49.8	99.9	61.5	10.0	999.9
70.0	161.2	24905.0	25.6	-48.9	99.9	60.2	11.9	222.2
70.5	161.5	25164.3	24.9	-48.0	99.9	59.2	13.6	999.9
71.0	161.9	25335.7	24.3	-48.7	99.9	50.4	15.3	999.9
71.5	162.2	29506.9	23.6	-48.6	\$9.9	57.1	15.1	999.9
72.0	162.5	25475.4	23.1	-48.4	99.9	55.2	13.5	999:9
72.5	162.8	25043.9	22.5	-48.3	99.9	52.7	11.9	999:9
73.0	163.1	26029.5	21.8	-48.2	99.9	49.7	10.7	999:9
73.5	163.3	26263.6	21.1	-48.2	99.9	47.1	11.2	999;9
74.8	163.6	26537.7	20.3	-48.3	99.9	44.8	11.6	999:3
- 24-8	148.8	26791.9	19.5	-48.3	99.9	42.7	12.3	999:9

.

الله المعادد المادد الم الم

۱۰۰. پښت

						14	APRII.	1981
						1818 G	HT	
TIME	CHTCT	HEIGHT	PRES	TEMP	DEW PT	DIR	SPEED	R HUM
MIN		GPH	MB	DG C	DG C	DG	M/SEC	PCT
75.0	164.1	27011.2	18.8	-48.2	99.9	40.1	12.3	999.9
75.5	164.3	27178.5	18.4	-47.7	99.9	36.1	11.6	999.9
76.0	164.5	27345.7	17.9	-47.2	99.9	31.6	10.8	999.9
76.5	164.8	27512.9	17.5	-46.8	99.9	26.4	10.2	999.9
77.0	165.0	27680.1	17.0	-46.3	99.9	20.7	9.7	999.9
77.5	165.2	27930.7	16.4	-45.4	99.9	999.9	99.9	999.9
78.0	165.4	28181.4	15.8	-44.5	99.9	999.9	99.9	999.9
78.5	165.6	28432.0	15.3	-43.6	99.9	995.9	99.9	999.9
79.0	165.8	28682.7	14.7	-42.7	99.9	999.9	99.9	999.9
79.5	166.0	28933.3	14.1	-41.8	99.9	999.9	99.9	999.9

APPROVAL

ATMOSPHERIC OBSERVATIONS FOR STS-1 LANDING

By Robert E. Turner, James E. Arnold, and Gregory S. Wilson

The information in this report has been reviewed for technical content. Review of any information concerning Department of Defense or nuclear energy activities or programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

WILLIAM W. VAUGHAN

Chief, Atmospheric Sciences Division

CHARLES A. LUNDQUIST

Director, Space Sciences Laboratory